



Safety Data Sheet

Copyright, 2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	07-4145-4	Version Number:	8.00
Issue Date:	04/27/22	Supersedes Date:	03/10/20

Product identifier

3M™ Marine High Strength Repair Filler PN's 46012, 46013, 46014

ID Number(s):

60-4551-1092-8, 60-9800-2720-9, 60-9800-2721-7, 60-9800-2722-5

7100036757, 7000120452, 7000000605, 7100231612

Recommended use

Marine Filler, Marine

Supplier's details

MANUFACTURER:	3M
DIVISION:	Automotive Aftermarket

ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

07-4142-1, 29-5993-0

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	07-4142-1	Version Number:	15.06
Issue Date:	05/10/21	Supersedes Date:	10/16/19

SECTION 1: Identification

1.1. Product identifier

3M™ Marine High Strength Repair Filler PN 46010 (6 fl. oz.); 46012 (pint); 46013 (quart); 46014 (gallon)

Product Identification Numbers

ID Number	UPC	ID Number	UPC
LB-T100-0197-2		LB-T100-0197-3	
LB-T100-0197-4			

1.2. Recommended use and restrictions on use

Recommended use

Marine Filler, Marine

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Automotive Aftermarket
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Flammable Solid: Category 1.
 Serious Eye Damage/Irritation: Category 2B.
 Carcinogenicity: Category 1A.
 Specific Target Organ Toxicity (single exposure): Category 1.
 Specific Target Organ Toxicity (single exposure): Category 3.
 Specific Target Organ Toxicity (repeated exposure): Category 1.
 Specific Target Organ Toxicity (repeated exposure): Category 2.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark | Health Hazard |

Pictograms



Hazard Statements

Flammable solid.

Causes eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause cancer.

Causes damage to organs:
liver |
sensory organs |

Causes damage to organs through prolonged or repeated exposure:
respiratory system |
sensory organs |

May cause damage to organs through prolonged or repeated exposure:
liver |

Precautionary Statements

General:

Keep out of reach of children.

Prevention:

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting equipment.
Do not breathe dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
Wear protective gloves and eye/face protection.
Do not eat, drink or smoke when using this product.
Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF exposed or concerned: Get medical advice/attention.
In case of fire: Use a fire fighting agent suitable for metal fires such as dry powder to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

34% of the mixture consists of ingredients of unknown acute oral toxicity.
34% of the mixture consists of ingredients of unknown acute dermal toxicity.
34% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Inert Filler	65997-17-3	10 - 30 Trade Secret *
Styrene Monomer	100-42-5	10 - 30 Trade Secret *
Vinyl Ester Resin	Trade Secret*	10 - 30 Trade Secret *
Wollastonite	13983-17-0	7 - 13 Trade Secret *
Polyester Resin	Trade Secret*	5 - 10 Trade Secret *
Synthetic Crystalline-Free Silica Gel	112926-00-8	3 - 7 Trade Secret *
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	1 - 5 Trade Secret *
Talc	14807-96-6	1 - 5 Trade Secret *
Polyester Polymer	Trade Secret*	1 - 5 Trade Secret *
Polyethylene	9002-88-4	0.5 - 1.5 Trade Secret *
Fiber	None	0.5 - 1.5 Trade Secret *
Quartz Silica	14808-60-7	< 0.5 Trade Secret *
Titanium Dioxide	13463-67-7	< 0.5 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you are concerned, get medical advice.

Skin Contact:

Wash with soap and water. If you are concerned, get medical advice.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you are concerned, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details. Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for metal fires such as dry powder to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Hydrocarbons
Carbon monoxide
Carbon dioxide
Toxic Vapor, Gas, Particulate

Condition

During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed to prevent loss of stabilizing materials. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Styrene Monomer	100-42-5	ACGIH	TWA:10 ppm;STEL:20 ppm	A3: Confirmed animal carcin., Ototoxicant
Styrene Monomer	100-42-5	OSHA	TWA:100 ppm;CEIL:200 ppm	
SILICA, AMORPHOUS	112926-00-8	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3	
SILICA, AMORPHOUS	112945-52-5	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3	
Titanium Dioxide	13463-67-7	ACGIH	TWA:10 mg/m3	A4: Not class. as human carcin
Titanium Dioxide	13463-67-7	OSHA	TWA(as total dust):15 mg/m3	
Wollastonite	13983-17-0	ACGIH	TWA(inhalable fraction):1 mg/m3	A4: Not class. as human carcin
Talc	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m3	A4: Not class. as human carcin
Talc	14807-96-6	OSHA	TWA concentration(respirable):0.1 mg/m3(2.4 millions of particles/cu. ft.);TWA:20 millions of particles/cu. ft.	
Quartz Silica	14808-60-7	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.
Quartz Silica	14808-60-7	OSHA	TWA Table Z-1(respirable):0.05 mg/m3;TWA Table Z-3(respirable):0.1 mg/m3;TWA concentration(respirable):0.1 mg/m3(2.4 millions of particles/cu. ft.)	
Inert Filler	65997-17-3	Manufacturer determined	TWA(as non-fibrous, respirable)(8 hours):3 mg/m3;TWA(as non-fibrous, inhalable fraction)(8 hours):10 mg/m3	
DUST, INERT OR NUISANCE	9002-88-4	OSHA	TWA(as total dust):15 mg/m3;TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m3);TWA(respirable fraction):5 mg/m3;TWA(respirable	

			fraction):15 millions of particles/cu. ft.(5 mg/m3)	
--	--	--	---	--

ACGIH : American Conference of Governmental Industrial Hygienists
 AIHA : American Industrial Hygiene Association
 CMRG : Chemical Manufacturer's Recommended Guidelines
 OSHA : United States Department of Labor - Occupational Safety and Health Administration
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
 Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Fluoroelastomer
 Polyvinyl Alcohol (PVA)
 Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
 Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
Physical state	Solid
Color	Gray-Brown
Specific Physical Form:	Paste
Odor	Pungent Styrene
Odor threshold	No Data Available
pH	No Data Available
Melting point	No Data Available
Boiling Point	293.00 °F [Details:CONDITIONS: (Styrene)]

Flash Point	88 °F [<i>Test Method:</i> Closed Cup] [<i>Details:</i> MIT data]
Evaporation rate	<i>No Data Available</i>
Flammability (solid, gas)	Flammable Solid: Category 1.
Flammable Limits(LEL)	1.1 % [<i>Details:</i> based on styrene]
Flammable Limits(UEL)	6.1 % [<i>Details:</i> based on styrene]
Vapor Pressure	4.3000 mmHg [<i>Details:</i> CONDITIONS: at 20 C (Styrene)]
Vapor Density	3.60 [<i>Ref Std:</i> AIR=1] [<i>Details:</i> CONDITIONS: (Styrene)]
Density	1.3 g/ml
Specific Gravity	1.3 [<i>Ref Std:</i> WATER=1]
Solubility in Water	Nil
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	740,000 - 999,999 centipoise
Hazardous Air Pollutants	27.7 % weight [<i>Test Method:</i> Calculated]
Hazardous Air Pollutants	0.77 lb HAPS/lb solids [<i>Test Method:</i> Calculated]
Volatile Organic Compounds	361 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1]
Volatile Organic Compounds	27.8 % weight [<i>Test Method:</i> calculated per CARB title 2]
Percent volatile	27.7 % weight
VOC Less H2O & Exempt Solvents	361 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1]
Solids Content	35.6 % weight

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable. May become unstable at increased temperatures and/or pressure.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat
Sparks and/or flames

10.5. Incompatible materials

Strong acids
Strong bases
Strong oxidizing agents
Alkali and alkaline earth metals

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be

reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause target organ effects:

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Prolonged or repeated exposure by inhalation may cause:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

Ocular Effects: Signs/symptoms may include blurred or significantly impaired vision.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
SILICA, CRYST AIRRESP	14808-60-7	Known human carcinogen	National Toxicology Program Carcinogens
Quartz Silica	14808-60-7	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Styrene Monomer	100-42-5	Grp. 2A: Probable human carc.	International Agency for Research on Cancer
Styrene Monomer	100-42-5	Anticipated human carcinogen	National Toxicology Program Carcinogens
Titanium Dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
Styrene Monomer	Dermal	Rat	LD50 > 2,000 mg/kg
Styrene Monomer	Inhalation-Vapor (4 hours)	Rat	LC50 11.8 mg/l
Styrene Monomer	Ingestion	Rat	LD50 5,000 mg/kg
Inert Filler	Dermal		LD50 estimated to be > 5,000 mg/kg
Inert Filler	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Wollastonite	Dermal		LD50 estimated to be > 5,000 mg/kg
Wollastonite	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Synthetic Crystalline-Free Silica Gel	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic Crystalline-Free Silica Gel	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic Crystalline-Free Silica Gel	Ingestion	Rat	LD50 > 5,110 mg/kg
Polyester Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Polyester Polymer	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Synthetic amorphous silica, fumed, crystalline-free	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic amorphous silica, fumed, crystalline-free	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Rat	LD50 > 5,110 mg/kg
Polyethylene	Dermal		LD50 estimated to be > 5,000 mg/kg
Polyethylene	Ingestion	Rat	LD50 > 2,000 mg/kg
Quartz Silica	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz Silica	Ingestion		LD50 estimated to be > 5,000 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Styrene Monomer	Professional judgement	Mild irritant
Inert Filler	Professional	No significant irritation

	judgement	
Synthetic Crystalline-Free Silica Gel	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation
Synthetic amorphous silica, fumed, crystalline-free	Rabbit	No significant irritation
Polyethylene	Professional judgement	No significant irritation
Quartz Silica	Professional judgement	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Styrene Monomer	Professional judgement	Moderate irritant
Inert Filler	Professional judgement	No significant irritation
Synthetic Crystalline-Free Silica Gel	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation
Synthetic amorphous silica, fumed, crystalline-free	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Styrene Monomer	Guinea pig	Not classified
Synthetic Crystalline-Free Silica Gel	Human and animal	Not classified
Synthetic amorphous silica, fumed, crystalline-free	Human and animal	Not classified
Titanium Dioxide	Human and animal	Not classified

Respiratory Sensitization

Name	Species	Value
Talc	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Styrene Monomer	In Vitro	Some positive data exist, but the data are not sufficient for classification
Styrene Monomer	In vivo	Some positive data exist, but the data are not sufficient for classification
Inert Filler	In Vitro	Some positive data exist, but the data are not sufficient for classification
Wollastonite	In Vitro	Not mutagenic
Synthetic Crystalline-Free Silica Gel	In Vitro	Not mutagenic
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic
Synthetic amorphous silica, fumed, crystalline-free	In Vitro	Not mutagenic

Quartz Silica	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz Silica	In vivo	Some positive data exist, but the data are not sufficient for classification
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Styrene Monomer	Ingestion	Mouse	Carcinogenic
Styrene Monomer	Inhalation	Human and animal	Carcinogenic
Inert Filler	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Synthetic Crystalline-Free Silica Gel	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Synthetic amorphous silica, fumed, crystalline-free	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Polyethylene	Not Specified	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Quartz Silica	Inhalation	Human and animal	Carcinogenic
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Styrene Monomer	Ingestion	Not classified for female reproduction	Rat	NOAEL 21 mg/kg/day	3 generation
Styrene Monomer	Inhalation	Not classified for female reproduction	Rat	NOAEL 2.1 mg/l	2 generation
Styrene Monomer	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.1 mg/l	2 generation
Styrene Monomer	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	60 days
Styrene Monomer	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during gestation
Styrene Monomer	Inhalation	Not classified for development	Multiple animal species	NOAEL 2.1 mg/l	during gestation
Synthetic Crystalline-Free Silica Gel	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic Crystalline-Free Silica Gel	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic Crystalline-Free Silica Gel	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation

Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
---	-----------	--------------------------------	-----	-----------------------	----------------------

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Styrene Monomer	Inhalation	auditory system	Causes damage to organs	Multiple animal species	LOAEL 4.3 mg/l	not available
Styrene Monomer	Inhalation	liver	Causes damage to organs	Mouse	LOAEL 2.1 mg/l	not available
Styrene Monomer	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	occupational exposure
Styrene Monomer	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Styrene Monomer	Inhalation	endocrine system	Not classified	Rat	NOAEL Not available	not available
Styrene Monomer	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2.1 mg/l	not available

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Styrene Monomer	Inhalation	auditory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL not available	occupational exposure
Styrene Monomer	Inhalation	eyes	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Styrene Monomer	Inhalation	liver	May cause damage to organs though prolonged or repeated exposure	Mouse	LOAEL 0.85 mg/l	13 weeks
Styrene Monomer	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	LOAEL 1.1 mg/l	not available
Styrene Monomer	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 0.85 mg/l	7 days
Styrene Monomer	Inhalation	endocrine system	Not classified	Rat	NOAEL 0.6 mg/l	10 days
Styrene Monomer	Inhalation	respiratory system	Not classified	Multiple animal species	LOAEL 0.09 mg/l	not available
Styrene Monomer	Inhalation	heart gastrointestinal tract bone, teeth, nails, and/or hair muscles kidney and/or bladder	Not classified	Multiple animal species	NOAEL 4.3 mg/l	2 years
Styrene Monomer	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 500 mg/kg/day	8 weeks
Styrene Monomer	Ingestion	immune system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	not available
Styrene Monomer	Ingestion	liver kidney and/or bladder	Not classified	Rat	NOAEL 677 mg/kg/day	6 months
Styrene Monomer	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 600 mg/kg/day	470 days
Styrene Monomer	Ingestion	heart respiratory system	Not classified	Rat	NOAEL 35 mg/kg/day	105 weeks
Inert Filler	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Wollastonite	Inhalation	respiratory system	Not classified	Human	NOAEL Not	occupational

					available	exposure
Wollastonite	Inhalation	pulmonary fibrosis	Not classified	Human and animal	NOAEL Not available	
Synthetic Crystalline-Free Silica Gel	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis respiratory system	Not classified	Rat	NOAEL 18 mg/m3	113 weeks
Synthetic amorphous silica, fumed, crystalline-free	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Quartz Silica	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

Name	Value
Styrene Monomer	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards
Flammable (gases, aerosols, liquids, or solids)

Health Hazards
Carcinogenicity
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Styrene Monomer	100-42-5	Trade Secret 10 - 30

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 3 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	07-4142-1	Version Number:	15.06
Issue Date:	05/10/21	Supersedes Date:	10/16/19

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer

may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	29-5993-0	Version Number:	6.00
Issue Date:	02/24/22	Supersedes Date:	12/07/21

SECTION 1: Identification

1.1. Product identifier

3M™ Cream Hardener (Red, White & Blue)

Product Identification Numbers

LB-K100-0965-7, LB-K100-0965-8, LB-K100-0965-9, LB-K100-0966-0, LB-K100-0966-1, LB-K100-0966-2, LB-K100-0966-3, LB-K100-1035-6, LB-K100-1045-4, LB-K100-1286-7, 41-0003-6674-4, 41-0003-6682-7, 41-0003-6685-0, 41-0003-6686-8, 41-0003-6687-6, 41-0003-7901-0, 41-0003-7903-6, 41-0003-7904-4, 41-0003-7922-6, 41-0003-7928-3, 41-0003-7930-9, 41-0003-7931-7, 41-0003-7932-5, 41-0003-7933-3, 41-0003-7935-8, 41-0003-7987-9, 41-0003-8059-6, 41-0003-8072-9, 41-0003-8073-7, 41-0003-8074-5, 41-0003-8146-1, 60-4550-6617-9, 60-4550-6830-8, 60-4550-6981-9, 60-4550-6982-7, 60-4550-8123-6, 60-4551-0388-1
7000120090, 7010327931, 7000120133, 7100191003

1.2. Recommended use and restrictions on use

Recommended use

Automotive, hardener for body fillers & glazes

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Automotive Aftermarket
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Organic Peroxide: Type E.
Serious Eye Damage/Irritation: Category 2A.
Skin Sensitizer: Category 1B.
Specific Target Organ Toxicity (single exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

Heating may cause a fire.

Causes serious eye irritation.

May cause an allergic skin reaction.

Causes damage to organs:

cardiovascular system |

nervous system |

kidney/urinary tract |

respiratory system |

Precautionary Statements**General:**

Keep out of reach of children.

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep away from clothing and other combustible materials.

Keep only in original container.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF exposed: Call a POISON CENTER or doctor/physician.

Specific treatment (see Notes to Physician on this label).

Storage:

Protect from sunlight.

Store at temperatures not exceeding 32C/90F. Keep cool.

Store locked up.

Store away from other materials.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Notes to Physician:

This product contains ethylene glycol. If there is reasonable suspicion of ethylene glycol poisoning, intravenous (IV) administration with either fomepizole (preferred) or ethanol (if fomepizole is unavailable) should be considered as part of the medical management.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Benzoyl Peroxide	94-36-0	30 - 60 Trade Secret *
Benzoic Acid, C9-11-Branched Alkyl Esters	131298-44-7	10 - 30 Trade Secret *
Water	7732-18-5	10 - 30 Trade Secret *
Calcium Sulfate	7778-18-9	1 - 10 Trade Secret *
Zinc Stearate	557-05-1	1 - 10 Trade Secret *
Ethylene Glycol	107-21-1	<= 7.5 Trade Secret *
Iron Oxide (FE2O3)	1309-37-1	<= 5 Trade Secret *
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	9038-95-3	<= 5 Trade Secret *
Ferric Ammonium Ferrocyanide	25869-00-5	<= 1 Trade Secret *
Ferric Ferrocyanide	14038-43-8	<= 1 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

This product contains ethylene glycol. If there is reasonable suspicion of ethylene glycol poisoning, intravenous (IV) administration with either fomepizole (preferred) or ethanol (if fomepizole is unavailable) should be considered as part of the medical management.

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode. Part of the oxygen for combustion is supplied by the peroxide itself.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Eliminate all ignition sources if safe to do so. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed. Protect from sunlight. Store away from heat. Store at temperatures not exceeding 32C/90F. Keep cool. Keep only in original container. Store away from other materials. Keep/store away from clothing and other combustible materials.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethylene Glycol	107-21-1	ACGIH	TWA(Vapor fraction):25 ppm;STEL(Vapor fraction):50 ppm;STEL(Inhalable aerosol):10 mg/m ³	A4: Not class. as human carcin
Iron Oxide (FE ₂ O ₃)	1309-37-1	ACGIH	TWA(respirable fraction):5 mg/m ³	A4: Not class. as human carcin

Iron Oxide (FE ₂ O ₃)	1309-37-1	OSHA	TWA(as fume):10 mg/m ³	
CYANIDES	14038-43-8	OSHA	TWA(as CN):5 mg/m ³	SKIN
Zinc Stearate	557-05-1	OSHA	TWA(as total dust):15 mg/m ³ ;TWA(respirable fraction):5 mg/m ³	
Calcium Sulfate	7778-18-9	ACGIH	TWA(inhalable fraction):10 mg/m ³	
Calcium Sulfate	7778-18-9	OSHA	TWA(as total dust):15 mg/m ³ ;TWA(respirable fraction):5 mg/m ³	
Benzoyl Peroxide	94-36-0	ACGIH	TWA:5 mg/m ³	A4: Not class. as human carcin
Benzoyl Peroxide	94-36-0	OSHA	TWA:5 mg/m ³	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide ventilation adequate to maintain dust concentration below minimum explosive concentrations. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Solid

Color

Red

Specific Physical Form:

Paste

Odor

Slight Ester

Odor threshold

No Data Available

pH

No Data Available

Melting point

No Data Available

Boiling Point

No Data Available

Flash Point

111 °C [*Test Method:Estimated*]

Evaporation rate

No Data Available

Flammability (solid, gas)

Organic Peroxide: Type E.

Flammable Limits(LEL)

Not Applicable

Flammable Limits(UEL)

Not Applicable

Vapor Pressure

Not Applicable

Vapor Density

Not Applicable

Density

1.2 g/cm³

Specific Gravity

1.2 [*@ 25 °C*] [*Ref Std:WATER=1*]

Solubility in Water

Negligible

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

No Data Available

Viscosity

No Data Available

Hazardous Air Pollutants

0 - 0.1209 lb HAPS/lb solids [*Test Method:Calculated*]

Molecular weight

Not Applicable

Volatile Organic Compounds

0 - 90 g/l [*Test Method:calculated SCAQMD rule 443.1*]

Volatile Organic Compounds

0 % weight [*Test Method:calculated per CARB title 2*]

Percent volatile

21 - 28.5 %

VOC Less H₂O & Exempt Solvents0 - 121 g/l [*Test Method:calculated SCAQMD rule 443.1*]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable. Stable unless exposed to heat, flames and drying conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Accelerators

10.6. Hazardous decomposition products

Substance

Carbon monoxide

Condition

Not Specified

Carbon dioxide
Toxic Vapor, Gas, Particulate

Not Specified
Not Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

May be harmful in contact with skin.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Cardiac Effects: Signs/symptoms may include irregular heartbeat (arrhythmia), changes in heart rate, damage to heart muscle, heart attack, and may be fatal.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
------	-------	---------	-------

Overall product	Dermal		No data available; calculated ATE >2,000 - ≤5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE >12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Benzoyl Peroxide	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Benzoyl Peroxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 24.3 mg/l
Benzoyl Peroxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Benzoic Acid, C9-11-Branched Alkyl Esters	Dermal	Rabbit	LD50 > 2,000 mg/kg
Benzoic Acid, C9-11-Branched Alkyl Esters	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5 mg/l
Benzoic Acid, C9-11-Branched Alkyl Esters	Ingestion	Rat	LD50 > 5,000 mg/kg
Calcium Sulfate	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Calcium Sulfate	Ingestion	Rat	LD50 > 5,000 mg/kg
Zinc Stearate	Dermal	Rabbit	LD50 > 2,000 mg/kg
Zinc Stearate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 50 mg/l
Zinc Stearate	Ingestion	Rat	LD50 > 5,000 mg/kg
Ethylene Glycol	Ingestion	Human	LD50 1,600 mg/kg
Ethylene Glycol	Inhalation-Dust/Mist (4 hours)	Other	LC50 estimated to be 5 - 12.5 mg/l
Ethylene Glycol	Dermal	Rabbit	9,530 mg/kg
Iron Oxide (FE2O3)	Dermal	Not available	LD50 3,100 mg/kg
Iron Oxide (FE2O3)	Ingestion	Not available	LD50 3,700 mg/kg
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Dermal	Rabbit	LD50 > 16,960 mg/kg
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5 mg/l
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	Rat	LD50 4,240 mg/kg
Ferric Ammonium Ferrocyanide	Dermal		LD50 estimated to be > 5,000 mg/kg
Ferric Ferrocyanide	Dermal		LD50 estimated to be > 5,000 mg/kg
Ferric Ammonium Ferrocyanide	Ingestion	Rat	LD50 > 5,110 mg/kg
Ferric Ferrocyanide	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Benzoyl Peroxide	Rabbit	Minimal irritation
Zinc Stearate	Rabbit	No significant irritation
Ethylene Glycol	Rabbit	Minimal irritation
Iron Oxide (FE2O3)	Rabbit	No significant irritation
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Benzoyl Peroxide	Rabbit	Severe irritant
Zinc Stearate	Rabbit	No significant irritation
Ethylene Glycol	Rabbit	Mild irritant
Iron Oxide (FE2O3)	Rabbit	No significant irritation
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Benzoyl Peroxide	Guinea pig	Sensitizing
Ethylene Glycol	Human	Not classified
Iron Oxide (FE2O3)	Human	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Benzoyl Peroxide	In Vitro	Not mutagenic
Benzoyl Peroxide	In vivo	Not mutagenic
Ethylene Glycol	In Vitro	Not mutagenic
Ethylene Glycol	In vivo	Not mutagenic
Iron Oxide (FE2O3)	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Benzoyl Peroxide	Ingestion	Multiple animal species	Not carcinogenic
Benzoyl Peroxide	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Ethylene Glycol	Ingestion	Multiple animal species	Not carcinogenic
Iron Oxide (FE2O3)	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Benzoyl Peroxide	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
Benzoyl Peroxide	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	prematuring & during gestation
Benzoyl Peroxide	Ingestion	Not classified for development	Rat	NOAEL 500 mg/kg/day	prematuring & during gestation
Ethylene Glycol	Dermal	Not classified for development	Mouse	NOAEL 3,549 mg/kg/day	during organogenesis
Ethylene Glycol	Ingestion	Not classified for development	Mouse	LOAEL 750 mg/kg/day	during organogenesis
Ethylene Glycol	Inhalation	Not classified for development	Mouse	NOAEL 1,000 mg/kg/day	during organogenesis
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation	Not classified for male reproduction	Rat	NOAEL 1 mg/l	2 weeks

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Ethylene Glycol	Ingestion	heart nervous system kidney and/or bladder respiratory system	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
Ethylene Glycol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Ethylene Glycol	Ingestion	liver	Not classified	Human	NOAEL Not available	poisoning and/or abuse
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	nervous system	Not classified	Rat	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Ethylene Glycol	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 200 mg/kg/day	2 years
Ethylene Glycol	Ingestion	vascular system	Not classified	Rat	NOAEL 200 mg/kg/day	2 years
Ethylene Glycol	Ingestion	heart hematopoietic system liver immune system muscles	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Ethylene Glycol	Ingestion	respiratory system	Not classified	Mouse	NOAEL 12,000 mg/kg/day	2 years
Ethylene Glycol	Ingestion	skin endocrine system bone, teeth, nails, and/or hair nervous system eyes	Not classified	Multiple animal species	NOAEL 1,000 mg/kg/day	2 years
Iron Oxide (FE2O3)	Inhalation	pulmonary fibrosis pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation	endocrine system hematopoietic system liver nervous system	Not classified	Rat	NOAEL 1 mg/l	2 weeks
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.005 mg/l	2 weeks
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation	respiratory system	Not classified	Rat	LOAEL 0.001 mg/l	2 weeks
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation	heart	Not classified	Rat	NOAEL 0.5 mg/l	2 weeks
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 145 mg/kg/day	90 days
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 500 mg/kg/day	2 years
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	heart endocrine system respiratory system	Not classified	Rat	NOAEL 3,770 mg/kg/day	90 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:**Physical Hazards**

Organic peroxide

Health Hazards

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Ethylene Glycol	107-21-1	Trade Secret <= 7.5
Zinc Stearate (ZINC COMPOUNDS)	557-05-1	Trade Secret 1 - 10
Benzoyl Peroxide	94-36-0	Trade Secret 30 - 60
Ferric Ferrocyanide (CYANIDES)	14038-43-8	Trade Secret <= 1

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** Oxidizer

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 4 **Flammability:** 1 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group:	29-5993-0	Version Number:	6.00
Issue Date:	02/24/22	Supersedes Date:	12/07/21

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com