

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version 1.27	Revision Date: 12/27/2023	SDS Number: F-1534098063	Date of last issue: 04/11/2023 Date of first issue: 06/10/2015
-----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

SECTION 1. IDENTIFICATION

Product name : ALEXSEAL P4420-Finish Primer 442 9806 white
Product code : 1534098063000

Manufacturer or supplier's details

Manufacturer, importer, supplier : Mankiewicz Coatings L.L.C
Address : 1200 Charleston Regional Parkway
Charleston, South Carolina 29492
USA
Telephone : +1 (843) 6547755
E-mail address : sdb_info@umco.de
Emergency telephone : USA Toll free +1 866 928 0789 EN/FR/ES(Carechem International)
Canada Toll free +1 800 579 7421 EN/FR (Carechem International)

Recommended use of the chemical and restrictions on use

Recommended use : Industrial serial painting

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 2
Skin irritation : Category 2
Serious eye damage : Category 1
Skin sensitization : Category 1
Carcinogenicity : Category 2
Specific target organ toxicity : Category 3 (Central nervous system)



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version 1.27	Revision Date: 12/27/2023	SDS Number: F-1534098063	Date of last issue: 04/11/2023 Date of first issue: 06/10/2015
-----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

- single exposure

Specific target organ toxicity : Category 2
- repeated exposure

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version 1.27	Revision Date: 12/27/2023	SDS Number: F-1534098063	Date of last issue: 04/11/2023 Date of first issue: 06/10/2015
-----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture of synthetic resins, organic solvents and pigments

Components

Chemical name	CAS-No.	Concentration (% w/w)
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	68082-29-1	>= 5 - < 12.5
titanium dioxide	13463-67-7	>= 5 - < 12.5
propan-2-ol	67-63-0	>= 5 - < 12.5
n-butyl acetate	123-86-4	>= 5 - < 12.5
kaolin	1332-58-7	>= 1 - < 5
butan-1-ol	71-36-3	>= 1 - < 5
1-methoxypropan-2-ol	107-98-2	>= 1 - < 5



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
1.27	12/27/2023	F-1534098063	Date of first issue: 06/10/2015

butanone	78-93-3	$\geq 1 - < 5$
xylenes	1330-20-7	$\geq 1 - < 5$
Amines, polyethylenepoly-, triethyl- enetetramine fraction	90640-67-8	$\geq 0.5 - < 1$
ethylbenzene	100-41-4	$\geq 0.25 - < 0.5$

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In all cases of doubt, or when sickness symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.
- If inhaled : Remove to fresh air, keep patient warm and at rest.
Irregular breathing/no breathing: artificial respiration.
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash skin thoroughly with soap and water or use recognised skin cleanser.
Do NOT use solvents or thinners !
- In case of eye contact : Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- If swallowed : Do NOT induce vomiting.
If accidentally swallowed obtain immediate medical attention.
Never give anything by mouth to an unconscious person.
Keep at rest.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause drowsiness or dizziness.
Suspected of causing cancer.
May cause damage to organs through prolonged or repeated exposure.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Alcohol resistant foam, CO2, powders



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version 1.27	Revision Date: 12/27/2023	SDS Number: F-1534098063	Date of last issue: 04/11/2023 Date of first issue: 06/10/2015
-----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Further information : Cool endangered containers with water in case of fire. DO NOT ALLOW RUN-OFF FROM FIRE FIGHTING TO ENTER DRAINS OR WATER COURSES!!
- Special protective equipment for fire-fighters : As in any fire, wear self-contained breathing apparatus pressure - demand, MSHA / NIOSH (approved or equivalent) and full protective gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Exclude sources of ignition and ventilate the area. Do not inhale vapors. Refer to protective measures listed in sections 7 and 8. Evacuate personnel to safe areas.
- Environmental precautions : Do not let product enter drains. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.
- Methods and materials for containment and cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing. No sparking tools should be used. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.
- Advice on safe handling : Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentrations higher than the



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version 1.27	Revision Date: 12/27/2023	SDS Number: F-1534098063	Date of last issue: 04/11/2023 Date of first issue: 06/10/2015
-----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

occupational exposure limits.
Comply with the health and safety at work laws.
Smoking, eating and drinking should be prohibited in the application area.
Observe specific national regulations for handling and use of paints.

- Conditions for safe storage : Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type. Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- Further information on storage conditions : Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep container dry in a cool, well-ventilated place.
- Materials to avoid : Keep away from oxidizing agents and strongly acid or alkaline materials.
- Recommended storage temperature : 41 - 95 °F / 5 - 35 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3	CA AB OEL
		TWA (Total dust)	10 mg/m3	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m3	CA BC OEL
		TWAEV (total dust)	10 mg/m3	CA QC OEL



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
 Product No.: 1534098063000

Version 1.27	Revision Date: 12/27/2023	SDS Number: F-1534098063	Date of last issue: 04/11/2023 Date of first issue: 06/10/2015
-----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

		TWA (Total dust)	10 mg/m3	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m3	CA BC OEL
propan-2-ol	67-63-0	TWA	200 ppm 492 mg/m3	CA AB OEL
		STEL	400 ppm 984 mg/m3	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	400 ppm	CA BC OEL
		TWAEV	200 ppm	CA QC OEL
		STEV	400 ppm	CA QC OEL
		VLE-PPT	200 ppm	NOM-010-STPS-2014
		VLE-CT	400 ppm	NOM-010-STPS-2014
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm 1,225 mg/m3	OSHA P0
n-butyl acetate	123-86-4	TWA	150 ppm 713 mg/m3	CA AB OEL
		STEL	200 ppm 950 mg/m3	CA AB OEL
		VLE-PPT	150 ppm	NOM-010-STPS-2014
		VLE-CT	200 ppm	NOM-010-STPS-2014
		TWA	150 ppm 710 mg/m3	NIOSH REL
		ST	200 ppm 950 mg/m3	NIOSH REL
		TWA	150 ppm 710 mg/m3	OSHA Z-1
		TWA	150 ppm 710 mg/m3	OSHA P0



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
 Product No.: 1534098063000

Version 1.27	Revision Date: 12/27/2023	SDS Number: F-1534098063	Date of last issue: 04/11/2023 Date of first issue: 06/10/2015
-----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

		STEL	200 ppm 950 mg/m3	OSHA P0
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
butan-1-ol	71-36-3	TWA	20 ppm 60 mg/m3	CA AB OEL
		TWA	15 ppm	CA BC OEL
		C	30 ppm	CA BC OEL
		C	50 ppm 152 mg/m3	CA QC OEL
		VLE-PPT	20 ppm	NOM-010- STPS-2014
		TWA	20 ppm	ACGIH
		C	50 ppm 150 mg/m3	NIOSH REL
		TWA	100 ppm 300 mg/m3	OSHA Z-1
		C	50 ppm 150 mg/m3	OSHA P0
1-methoxypropan-2-ol	107-98-2	STEL	150 ppm 553 mg/m3	CA AB OEL
		TWA	100 ppm 369 mg/m3	CA AB OEL
		TWA	50 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL
		TWAEV	100 ppm 369 mg/m3	CA QC OEL
		STEV	150 ppm 553 mg/m3	CA QC OEL
		VLE-PPT	100 ppm	NOM-010- STPS-2014
		VLE-CT	150 ppm	NOM-010- STPS-2014
		TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
		ST	150 ppm 540 mg/m3	NIOSH REL
		TWA	100 ppm 360 mg/m3	NIOSH REL
		TWA	100 ppm 360 mg/m3	OSHA P0
		STEL	150 ppm 540 mg/m3	OSHA P0
butanone	78-93-3	TWA	200 ppm 590 mg/m3	CA AB OEL



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
 Product No.: 1534098063000

Version 1.27	Revision Date: 12/27/2023	SDS Number: F-1534098063	Date of last issue: 04/11/2023 Date of first issue: 06/10/2015
-----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

		STEL	300 ppm 885 mg/m3	CA AB OEL
		TWA	50 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL
		TWAEV	50 ppm 150 mg/m3	CA QC OEL
		STEV	100 ppm 300 mg/m3	CA QC OEL
		VLE-PPT	200 ppm	NOM-010- STPS-2014
		VLE-CT	300 ppm	NOM-010- STPS-2014
		TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
		TWA	200 ppm 590 mg/m3	NIOSH REL
		ST	300 ppm 885 mg/m3	NIOSH REL
		TWA	200 ppm 590 mg/m3	OSHA Z-1
		TWA	200 ppm 590 mg/m3	OSHA P0
		STEL	300 ppm 885 mg/m3	OSHA P0
xylenes	1330-20-7	VLE-PPT	100 ppm	NOM-010- STPS-2014
		VLE-CT	150 ppm	NOM-010- STPS-2014
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	20 ppm	ACGIH
		STEL	150 ppm 651 mg/m3	CA AB OEL
		TWA	100 ppm 434 mg/m3	CA AB OEL
		TWAEV	100 ppm 434 mg/m3	CA QC OEL
		STEV	150 ppm 651 mg/m3	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		STEL	150 ppm 655 mg/m3	OSHA P0
		TWA	100 ppm 435 mg/m3	OSHA P0



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version 1.27	Revision Date: 12/27/2023	SDS Number: F-1534098063	Date of last issue: 04/11/2023 Date of first issue: 06/10/2015
-----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

ethylbenzene	100-41-4	TWA	100 ppm 434 mg/m3	CA AB OEL
		STEL	125 ppm 543 mg/m3	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		VLE-PPT	20 ppm	NOM-010- STPS-2014
		TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	MX BEI
		Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI
butanone	78-93-3	MEK	Urine	End of shift	2 mg/l	MX BEI
		methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI
xylenes	1330-20-7	Methyl-hippuric	Urine	End of shift (As	1.5 g/g cre-atinine	ACGIH BEI



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
 Product No.: 1534098063000

Version 1.27	Revision Date: 12/27/2023	SDS Number: F-1534098063	Date of last issue: 04/11/2023 Date of first issue: 06/10/2015
-----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

		acids		soon as possible after exposure ceases)		
		Methyl-hippuric acid	Urine	End of shift	1.5 g/g creatinine	MX BEI
ethylbenzene	100-41-4	Sum of Mandelic acid plus phenylglyoxylic acid	Urine	End of shift at end of work-week	0.7 g/g creatinine	MX BEI
		Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

Engineering measures : Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain aerosol- and solvent vapors concentration below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection : If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Use MSHA/NIOSH approved respirator if concentration exceeds recommended exposure levels. Dry grinding, torch cutting and/or welding however can produce hazardous dust and/or vapor. If possible, machine employing a wet medium. Where practicable, install exhaust hoods to improve capture of vapors and fumes and avoid exposition; otherwise wear respiratory protection equipment.

Hand protection

Remarks : Glove permeation data does not exist for this material. The following glove(s) should be used for splash protection only:
 Appropriate material: nitrile



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version 1.27	Revision Date: 12/27/2023	SDS Number: F-1534098063	Date of last issue: 04/11/2023 Date of first issue: 06/10/2015
-----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

- Eye protection : Use safety glasses or face shield (ANSI Z87.1 or approved equivalent).
- Skin and body protection : Depending on the probability of the occurrence of dangerously explosive atmospheres, adapted protective clothing must be worn.
- Protective measures : Do not eat or drink during work - no smoking.
Avoid product contact with skin, eyes and clothing.
Avoid the inhalation of dust from sanding, particulates and spray mist arising from the application of this preparation.
When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapor in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process until such time as the particulates and solvent vapor concentration has fallen below the exposure limits.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid (68 - 77 °F / 20 - 25 °C, 1,013 hPa)
- Color : according product name
- Odor : characteristic
- pH : 6 - 8 (68 °F / 20 °C)
Concentration: 10 %
: No data available
- Boiling point/boiling range : ca. 248 °F / 120 °C
- Flash point : 50.9 °F / 10.5 °C
Method: ISO 13736



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version 1.27	Revision Date: 12/27/2023	SDS Number: F-1534098063	Date of last issue: 04/11/2023 Date of first issue: 06/10/2015
-----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

Flammability (liquids)	:	No data available
Upper explosion limit / Upper flammability limit	:	10 %(V)
Lower explosion limit / Lower flammability limit	:	1 %(V)
Vapor pressure	:	ca. 100 hPa (122 °F / 50 °C)
Relative density	:	No data available
Density	:	12.43 lb/gal (1.49 g/cm ³) (68 °F / 20 °C)
Solubility(ies) Water solubility	:	insoluble
Autoignition temperature	:	> 752 °F / > 400 °C
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	> 21 mm ² /s
Flow time	:	> 200 s Cross section: 4 mm Method: DIN 53211 > 101 s Cross section: 6 mm Method: ISO 2431

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	No dangerous reaction known under conditions of normal use. There are no data available on the preparation itself.
Conditions to avoid	:	Stable under recommended storage and handling conditions (See section 7).



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version 1.27	Revision Date: 12/27/2023	SDS Number: F-1534098063	Date of last issue: 04/11/2023 Date of first issue: 06/10/2015
-----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

- Incompatible materials : Keep away from oxidizing agents, strongly alkaline and strongly acidic materials in order to avoid exothermic reactions.
- Hazardous decomposition products : When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Product:

- Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method
- Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method
- Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

butan-1-ol:

- Acute oral toxicity : LD50 (Rat): 790 mg/kg

1-methoxypropan-2-ol:

- Acute oral toxicity : LD50 Oral (Rat, male and female): 4,016 mg/kg
Method: Regulation (EC) No. 440/2008, Annex, B.1 tris
- Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Method: Regulation (EC) No. 440/2008, Annex, B.3

Amines, polyethylenepoly-, triethylenetetramine fraction:

- Acute oral toxicity : LD50 (Rat, female): 1,591.4 mg/kg
- Acute dermal toxicity : LD50 (Rabbit, male and female): 1,465.4 mg/kg



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version 1.27	Revision Date: 12/27/2023	SDS Number: F-1534098063	Date of last issue: 04/11/2023 Date of first issue: 06/10/2015
-----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Suspected of causing cancer.

IARC	Group 1: Carcinogenic to humans kaolin (Silica dust, crystalline)	1332-58-7
	Group 2B: Possibly carcinogenic to humans titanium dioxide	13463-67-7
	Group 2B: Possibly carcinogenic to humans ethylbenzene	100-41-4
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.	
NTP	Known to be human carcinogen kaolin (Silica, Crystalline (Respirable Size))	1332-58-7

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified due to lack of data.



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version 1.27	Revision Date: 12/27/2023	SDS Number: F-1534098063	Date of last issue: 04/11/2023 Date of first issue: 06/10/2015
-----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

Further information

Product:

Remarks : Exposure of vapor concentration in excess of the stated OEL's may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue muscular weakness, drowsiness and in extrem cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : There are no data available on the preparation itself.

Components:

Amines, polyethylenepoly-, triethylenetetramine fraction:

Toxicity to algae/aquatic plants : ErC50 (Selenastrum capricornutum (green algae)): 20 mg/l
Exposure time: 72 h
Test Type: semi-static test
Method: OECD Test Guideline 201

Persistence and degradability

Product:

Biodegradability : Remarks: There are no data available on the preparation itself.

Components:

propan-2-ol:

Biodegradability : Result: rapidly biodegradable
Biodegradation: 95 %



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version 1.27	Revision Date: 12/27/2023	SDS Number: F-1534098063	Date of last issue: 04/11/2023 Date of first issue: 06/10/2015
-----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

Exposure time: 21 d

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: There are no data available on the preparation itself.

Mobility in soil

Product:

Mobility : Remarks: There are no data available on the preparation itself.

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : There are no data available on the preparation itself.

The product should not be allowed to enter drains or water courses.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed off in agreement with the regional waste disposal company.



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
1.27	12/27/2023	F-1534098063	Date of first issue: 06/10/2015

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1263
Proper shipping name : PAINT
(trizinc bis(orthophosphate), Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine)
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : II
Labels : FLAMMABLE LIQUID
Marine pollutant : yes(trizinc bis(orthophosphate), Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version 1.27	Revision Date: 12/27/2023	SDS Number: F-1534098063	Date of last issue: 04/11/2023 Date of first issue: 06/10/2015
-----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Chronic Health Hazard
Flammable (gases, aerosols, liquids, or solids)
Respiratory or skin sensitization
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

propan-2-ol	67-63-0	>= 5 - < 10 %
trizinc bis(orthophospha te)	7779-90-0	>= 5 - < 10 %
butan-1-ol	71-36-3	>= 1 - < 5 %
xylenes	1330-20-7	>= 1 - < 5 %
ethylbenzene	100-41-4	>= 0.1 - < 1 %
zinc oxide	1314-13-2	>= 0.1 - < 1 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

xylenes	1330-20-7	>= 1 - < 5 %
ethylbenzene	100-41-4	>= 0.1 - < 1 %



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version 1.27	Revision Date: 12/27/2023	SDS Number: F-1534098063	Date of last issue: 04/11/2023 Date of first issue: 06/10/2015
-----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

VOC content excluding water : 3.5 lb/gal (414 g/l)

For the calculation of VOC values in this section all substances have been considered which fall under the definition of VOC according to 40 CFR 51.100. Additionally, the calculation complies with the requirements of SCAQMD Rule 1106.1, amended February 12, 1999.

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

propan-2-ol	67-63-0	>= 5 - < 10 %
n-butyl acetate	123-86-4	>= 5 - < 10 %
butan-1-ol	71-36-3	>= 1 - < 5 %
butanone	78-93-3	>= 1 - < 5 %
xylenes	1330-20-7	>= 1 - < 5 %

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

n-butyl acetate	123-86-4	>= 5 - < 10 %
xylenes	1330-20-7	>= 1 - < 5 %
ethylbenzene	100-41-4	>= 0.1 - < 1 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

n-butyl acetate	123-86-4	>= 5 - < 10 %
xylenes	1330-20-7	>= 1 - < 5 %
ethylbenzene	100-41-4	>= 0.1 - < 1 %

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

trizinc bis(orthophosphate)	7779-90-0	>= 5 - < 10 %
-----------------------------	-----------	---------------

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

limestone	1317-65-3
propan-2-ol	67-63-0
n-butyl acetate	123-86-4
kaolin	1332-58-7
butan-1-ol	71-36-3
1-methoxypropan-2-ol	107-98-2
butanone	78-93-3
xylenes	1330-20-7

Pennsylvania Right To Know

limestone	1317-65-3
-----------	-----------



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version 1.27	Revision Date: 12/27/2023	SDS Number: F-1534098063	Date of last issue: 04/11/2023 Date of first issue: 06/10/2015
-----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

propan-2-ol	67-63-0
n-butyl acetate	123-86-4
trizinc bis(orthophosphate)	7779-90-0
kaolin	1332-58-7
butan-1-ol	71-36-3
1-methoxypropan-2-ol	107-98-2
butanone	78-93-3
xylenes	1330-20-7
ethylbenzene	100-41-4
aluminium oxide (Smoke)	1344-28-1
zinc oxide	1314-13-2

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

butanone	78-93-3
ethylbenzene	100-41-4

Washington Chemicals of High Concern

butanone	78-93-3
ethylbenzene	100-41-4

California Prop. 65

WARNING: This product can expose you to chemicals including kaolin, ethylbenzene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

propan-2-ol	67-63-0
n-butyl acetate	123-86-4
trizinc bis(orthophosphate)	7779-90-0
butan-1-ol	71-36-3
1-methoxypropan-2-ol	107-98-2
butanone	78-93-3
xylenes	1330-20-7

California Permissible Exposure Limits for Chemical Contaminants

titanium dioxide	13463-67-7
propan-2-ol	67-63-0
n-butyl acetate	123-86-4
butan-1-ol	71-36-3
1-methoxypropan-2-ol	107-98-2
butanone	78-93-3
xylenes	1330-20-7

California Regulated Carcinogens

kaolin	1332-58-7
--------	-----------



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version 1.27	Revision Date: 12/27/2023	SDS Number: F-1534098063	Date of last issue: 04/11/2023 Date of first issue: 06/10/2015
-----------------	------------------------------	-----------------------------	-------------------------------------------------------------------


The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	*	3
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Health
0=Slightly Hazardous Slightly Hazardous
2=Hazardous
3=Extreme danger
4=Deadly

Flammability
0=Will not burn
2=Flashpoint below 200 F
3=Flashpoint below 100 F
4=Flashpoint below 73 F

Instability
0=Stable
1=Unstable if heated
2=Violent chemical reaction; water reactive
3=Shock or heat may detonate
4=May detonate

Special hazard
SA Simple Asphyxiant
ACID Acid



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
1.27	12/27/2023	F-1534098063	Date of first issue: 06/10/2015

OX Oxidizer
W Water Reactive
CORR Corrosive

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL : Canada. British Columbia OEL
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
MX BEI : Official Mexican Norm NOM-047-SSA1-2011, Environmental Health - Biological exposure indices for workers occupationally exposed to chemical agents
NIOSH REL : USA. NIOSH Recommended Exposure Limits
NOM-010-STPS-2014 : Mexico. Norm NOM-010-STPS-2014 on Chemicals Polluting the Work Environment - Identification, Assessment and Control - Appendix 1 Occupational Exposure Limits
OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA BC OEL / STEL : short-term exposure limit
CA BC OEL / C : ceiling limit
CA QC OEL / TWA EV : Time-weighted average exposure value
CA QC OEL / STEV : Short-term exposure value
CA QC OEL / C : Ceiling
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C : Ceiling value not be exceeded at any time.
NOM-010-STPS-2014 / VLE-PPT : Time weighted average limit value
NOM-010-STPS-2014 / VLE-CT : Short term exposure limit value
OSHA P0 / TWA : 8-hour time weighted average
OSHA P0 / STEL : Short-term exposure limit
OSHA P0 / C : Ceiling limit
OSHA Z-1 / TWA : 8-hour time weighted average



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
1.27	12/27/2023	F-1534098063	Date of first issue: 06/10/2015

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information given in this material safety data sheet does not release the user from its duty of risk assessment and control in the work place defined in other health and safety law.

Adhere to the national sanitary and occupational safety regulations when using this product.

This SDS have been created to comply with The Hazard Communication Standard (HCS)(29 CFR

1910.1200).

This SDS have been created to comply with the Hazardous Products Regulations(SOR/2015-17).

Revision Date : 12/27/2023



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P4420-Finish Primer 442
Product No.: 1534098063000

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
1.27	12/27/2023	F-1534098063	Date of first issue: 06/10/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8

