MATERIAL SAFE	TY DATA SHEET		Sales Order: {SalesOrd}
D3002 HIGH BUILD CONVERTER		MSDS Revision No: MSDS Revision Date:	E2 -0 07/27/2004
	Akzo Nobel Coatings	EMERGENCY NUMBERS:	
AULGRIP	Awlgrip North America 2270 Morris Avenue	(800) 424-9300 (703) 527-3887	CHEMTREC (USA) CHEMTREC (Intl) Poison Control
	P. O. Box 386 Union, NJ 07083	(800) 854-6813 CUSTOMER SERVICE: (888) 355-3090	Center (Non-Emergency) AWLGRIP (Phone)
		(908) 686-1752	AWLGRIP (Fax)

1. GENERAL INFORMATION

Product Identity: D3002 HIGH BUILD CONVERTER

Bulk Sales Reference No: OD3002

IMPORTANT: Read this MSDS before handling or disposing of this product, and provide this information to the employee, customers, and users of this product. PLEASE NOTE THE MSDS REVISION NUMBER AT THE TOP OF THIS PAGE. If the MSDS Revision Number posted at the top of this page does not match the MSDS Revision Number on the product label, please contact Customer Service at the phone number included above for the correct MSDS. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. **NOTICE:** OSHA hazardous chemicals are listed in Section 2 if present at 1% or more. Carcinogens and extraordinarily/special hazardous chemicals are listed in Section 2 if present at .1% or more. Additional regulatory information for specific chemical categories is included in Section 15.

CAS No.	Ingredient Name & %	Source	Exposure Data
		OSHA:	200 ppm TWA; 590 mg/m3 TWA300 ppm STEL; 885 mg/m3 STEL
		ACGIH:	200 ppm TWA300 ppm STEL
		NIOSH:	200 ppm TWA; 590 mg/m3 TWA300 ppm STEL; 885 mg/m3 STEL3000 ppm IDLH

2. HAZARDOUS INGREDIENT INFORMATION

000078-93-3	Methyl ethyl ketone 1.0 - 10% by Weight	Supplier: OHSA, CAN: Mexico: Brazil:	No Data Available200 ppm TWAEV; 590 mg/m3 TWAEV300 ppm STEV; 885 mg/m3m3 STEV200 ppm TWA; 590 mg/m3 TWA300 ppm STEL; 885 mg/m3STEL155 ppm TWA; 460 mg/m3 TWA
		Source	Health Data
		NIOSH:	Irritation; liver kidney
		Source	Carcinogen Data
		OSHA:	Select Carcinogen: No
		NTP:	Known Carcinogen: No; Suspected Carcinogen: No
		IARC:	Group 1: No; Group 2A: No; Group 2b: No; Group 3: No; Group 4: No

CAS No.	Ingredient Name & %	Source	Exposure Data	
		OSHA:	200 ppm TWA150 ppm STEL; 560 mg/m3 STEL	
			ACGIH:	50 ppm TWA
		NIOSH:	100 ppm TWA; 375 mg/m3 TWA150 ppm STEL; 560 mg/m3 STEL500 ppm IDLH	
		Supplier:	No Data Available	
		OHSA, CAN:	50 ppm TWAEV; 376 mg/m3 TWAEV	
	Talaana	Mexico:	100 ppm TWA; 375 mg/m3 TWA	
000108-88-3	Toluene 1.0 - 10% by Weight	Brazil:	78 ppm TWA; 290 mg/m3 TWA	
		Source	Health Data	
		NIOSH:	Central nervous system depressant	
		Source	Carcinogen Data	
		OSHA:	Select Carcinogen: No	
		NTP:	Known Carcinogen: No; Suspected Carcinogen: No	
		IARC:	Group 1: No; Group 2A: No; Group 2b: No; Group 3: Yes; Group 4: No	

CAS No.	Ingredient Name & %	Source	Exposure Data
		OSHA:	200 ppm TWA; 740 mg/m3 TWA
		ACGIH:	5 ppm TWA
		NIOSH:	0.5 ppm TWA; 1.8 mg/m3 TWA500 ppm IDLH

		Supplier:	No Data Available
	000110-80-5	OHSA, CAN:	5 ppm TWAEV; 18 mg/m3 TWAEV
000110-80-5		Mexico:	50 ppm TWA; 185 mg/m3 TWA100 ppm STEL; 370 mg/m3 STEL
	1.0 - 10% by Weight	Brazil:	78 ppm TWA; 290 mg/m3 TWA
		Source	Health Data
		NIOSH:	Reproductive and developmental effects; blood CNS
		Courses	Carcinogen Data
		Source	Cal childgen Data
		OSHA:	Select Carcinogen: No
			C

CAS No.	Ingredient Name & %	Source	Exposure Data
		OSHA:	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
		ACGIH:	10 mg/m3 TWA
		NIOSH:	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)50 mg/m3 IDLH (as Ba, except barium sulfate)
		Supplier:	No Data Available
		OHSA, CAN:	10 mg/m3 TWAEV (total dust)
	Devision on life to	Mexico:	0.5 mg/m3 TWA
007727-43-7	Barium sulfate 50 - 75% by Weight	Brazil:	No Data Available
		Source	Health Data
		NIOSH:	Eye nose
		Source	Carcinogen Data
		OSHA:	Select Carcinogen: No
		NTP:	Known Carcinogen: No; Suspected Carcinogen: No
		IARC:	Group 1: No; Group 2A: No; Group 2b: No; Group 3: No; Group 4: No

CAS No.	Ingredient Name & %	Source	Exposure Data
		OSHA:	No Data Available
		ACGIH:	2 mg/m3 TWA (respirable fraction, particulate matter containing no asbestos and <1% crystallin

		NIOSH:	2 mg/m3 TWA (respirable dust, containing no asbestos and less than 1% quartz)1000 mg/m3 IDLH (containing no asbestos and less than 1% quartz)
		Supplier:	No Data Available
014807-96-6	Talc	OHSA, CAN:	2 mg/m3 TWAEV (respirable dust)
	1.0 - 10% by Weight	Mexico:	No Data Available
		Brazil:	No Data Available
		Source	Health Data
		NIOSH:	(containing asbestos); Fibrotic pneumoconiosis; (containing no asbestos); Nonmalignant respiratory effects
		Source	Carcinogen Data
		OSHA:	Salast Carring gan. Vas
		OSIIA.	Select Carcinogen: Yes
		NTP:	Known Carcinogen: No; Suspected Carcinogen: No

CAS No.	Ingredient Name & %	Source	Exposure Data
		OSHA:	No Data Available
		ACGIH:	No Data Available
		NIOSH:	No Data Available
		Supplier:	No Data Available
		OHSA, CAN:	No Data Available
	Polymer of epoxy resin and	Mexico:	No Data Available
025036-25-3	bisphenol A	Brazil:	No Data Available
	10 - 25% by Weight	Source	Health Data
		NIOSH:	No Data Available
		Source	Carcinogen Data
		OSHA:	Select Carcinogen: No
		NTP:	Known Carcinogen: No; Suspected Carcinogen: No
		IARC:	Group 1: No; Group 2A: No; Group 2b: No; Group 3: No; Group 4: No

3. HAZARD IDENTIFICATION

Overview:	permanent brain and nervous sy the contents may be harmful or	ted repeated and prolonged occupational of ystem damage. Intentional misuse by delib fatal. Avoid contact with eyes, skin and co disorders based on animal data (See Section	erately concentrating and inhaling lothing. Contains an ingredient
Inhalation:	Harmful if inhaled. Causes lung nervous system causing dizzine	g irritation. Causes nose and throat irritations, headache or nausea.	on. Vapors may affect the brain or
Eyes:	Causes severe eye irritation. Do	o not get in eyes.	
Skin:	Causes skin irritation. May cause	se allergic skin reaction. May be harmful i	f absorbed through the skin.
Ingestion:	Harmful if swallowed. May cau	se abdominal pain, nausea, vomiting, diar	rhea, or drowsiness.
Chronic Effects:	Cancer hazard. Contains an ing	an cause organ damage (See Section 2 and redient which can cause cancer (See Section ends on duration and level of exposure.	C
HMIS Rating:	Health: Unknown	Flammability: Unknown	Reactivity: Unknown

4. FIRST AID MEASURES

General:	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin:	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion:	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

5. PROTECTIVE EQUIPMENT AND CONTROL MEASURES

Respiratory:	 Select equipment to provide protection from the ingredients listed in Section 2 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes:	Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

Skin/Hand:	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls:	Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.
Other Work Practices:	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

6. FIRE AND EXPLOSION INFORMATION

Flash Point:	F: 20
	C: -7
Lower Explosive Limit (LEL):	1 (%vol in air) at Normal Atmospheric Temp and Pressure
Fire and Explosion Hazards:	Extremely flammable liquid and vapor. Vapors may cause flash fire. FLAMMABLE/ COMBUSTIBLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated.
Fire Fighting Procedures:	CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. SMALL FIRES: Use dry chemical, CO2, water spray or alcohol-resistant foam. LARGE FIRES: Use water spray, fog, or alcohol-resistant foam. Do not use straight streams. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material. Also Reference Emergency Response Guide Number: 127

7. PHYSICAL AND CHEMICAL PROPERTIES

p		
Physical State:	Liquid	
pH:	Not Determined	
Specific Gravity:	1.816514	
Boiling Point (F):	175	
Vapor Density:	Heavier than air	
VOC Content (lbs):	ontent (lbs): Refer to the Technical Data Sheet for this product.	
Evaporation Rate:	Slower than ether	

8. STABILITY AND REACTIVITY DATA

General:	This product is stable and hazardous polymerization will not occur.
Incompatible Materials:	Strong oxidizing agents.
Hazardous Decompostion:	May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

9. HANDLING AND STORAGE

Storage Temperature:	Store between 32 and 120 F		
Handling and Storage Precautions:	Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Do not get in eyes, on skin or clothing. Close container after each use. Wash thoroughly after handling.		

10. TOXICOLOGICAL DATA

Section 2 for chemical specific data.	General:	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See

11. ECOLOGICAL DATA

General: No additional information provided for this product. See Section 2 for chemical specific data.

12. ACCIDENTAL RELEASE MEASURES

	ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area).
	Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk
Spill Response	through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers,
Procedures:	basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover
	with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking
	tools to collect absorbed material.
	CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately
	for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay
Public Safety:	upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider
	initial downwind evacuation for at least 300 meters (1000 feet).
	Also, Reference Emergency Response Guide Number: 127

13. DISPOSAL CONSIDERATION

Waste Disposal:Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in
Section 15 if listed).

14. TRANSPORTATION INFORMATION

DOT (Domestic Surface Transportation)		IMO / IN	MDG (Ocean Transportation)
DOT Proper Shipping Name:		IMDG Proper Shipp	ing Name:
PAINT		PAINT	
	2	IMDG Hazard	3.2 - Intermediate flashpoint flammable
DOT Hazard Class:	3	Class:	liquids
UN / NA Number:	UN 1263	UN Number:	UN 1263
	ш	IMDG Packing	TT
DOT Packing Group:	II	Group:	II
CEDCI A/DOT DO.	840 gal. / 12714 lbs.	System Reference	28
CERCLA/DOT RQ:		Code:	28

15. REGULATORY INFORMATION

Regulatory Overview:	The regulatory data in Section 15 is not intended to be all- inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory. Note: Any chemical ingredients listed in Section 15, that do not also appear in Section 2, are contained in the product at a concentration below the applicable OSHA threshold level of 1% or 0.1%.
WHMIS Classification:	Not Determined

Regulatory List	Product Ingredients on List
DOT Marine Pollutants	
(10%):	
(No Product	
Ingredients Listed)	
DOT Severe Marine	
Pollutants (1%):	
(No Product	
Ingredients Listed)	
EPCRA 311/312	
Chemicals and RQs	
(>.1%):	
000110-80-5	ETHOXYETHANOL : 1000 lb final RQ; 454 kg final RQ
000078-93-3	Methyl ethyl ketone : 5000 lb final RQ; 2270 kg final RQ
000123-86-4	n-Butyl acetate : 5000 lb final RQ; 2270 kg final RQ
000108-88-3	Toluene : 1000 lb final RQ; 454 kg final RQ
001330-20-7	Xylenes (o-, m-, p- isomers) : 100 lb final RQ; 45.4 kg final RQ
EPCRA 302 Extremely	
Hazardous (>.1%) :	
(No Product	
Ingredients Listed)	
EPCRA 313 Toxic	
Chemicals (>.1%) :	
007727-43-7	Barium sulfate
000111-76-2	BUTOXYETHANOL
000110-80-5	ETHOXYETHANOL
000078-93-3	Methyl ethyl ketone
000108-88-3	Toluene
001330-20-7	Xylenes (o-, m-, p- isomers)
Mass RTK Substances	
(>1%):	
007727-43-7	Barium sulfate
000110-80-5	ETHOXYETHANOL
000078-93-3	Methyl ethyl ketone
014807-96-6	Talc
000108-88-3	Toluene
Mass Extraordinarily	
Haz Sub (>.01%) : (No Product	
(No Product Ingredients Listed)	
Penn RTK Substances	
(>1%):	
007727-43-7	Barium sulfate
000110-80-5	ETHOXYETHANOL
000078-93-3	Methyl ethyl ketone
014807-96-6	Talc
000108-88-3	Toluene
Penn Special Hazardous	
Substances (>.01%) :	
000108-88-3	Toluene
Rhode Island Hazardous	
Substances (>.1%) :	
· · /	

000111-76-2	BUTOXYETHANOL
000110-80-5	ETHOXYETHANOL
000064-17-5	Ethyl alcohol
000078-93-3	Methyl ethyl ketone
000123-86-4	n-Butyl acetate
014807-96-6	Talc
000108-88-3	Toluene
001330-20-7	Xylenes (o-, m-, p- isomers)
RCRA Status (>.01%) :	
000078-93-3	Methyl ethyl ketone : 200.0 mg/L regulatory level; waste number D035
N.J. RTK Substances	
(>1%):	
000110-80-5	ETHOXYETHANOL
000078-93-3	Methyl ethyl ketone
014807-96-6	Talc
000108-88-3	Toluene
N.J. Special Hazardous	
Substances (>.01%) :	
000064-17-5	Ethyl alcohol
000067-56-1	Methyl alcohol
000078-93-3	Methyl ethyl ketone
000123-86-4	n-Butyl acetate
000108-88-3	Toluene
001330-20-7	Xylenes (o-, m-, p- isomers)
N.J. Env. Hazardous	
Substances (>.1%) :	
007727-43-7	Barium sulfate
000111-76-2	BUTOXYETHANOL
000110-80-5	ETHOXYETHANOL
000078-93-3	Methyl ethyl ketone
000108-88-3	Toluene
001330-20-7	Xylenes (o-, m-, p- isomers)
Proposition 65 -	
Carcinogens (>0%):	
014807-96-6	Talc
000108-88-3	Toluene
Proposition 65 - Female	
Repro Toxins (>0%):	
(No Product	
Ingredients Listed)	
Proposition 65 - Male	
Repro Toxins (>0%):	
000110-80-5	ETHOXYETHANOL
Proposition 65 -	
Developmental Toxins	
(> 0%):	
000110-80-5	ETHOXYETHANOL
000064-17-5	Ethyl alcohol
000108-88-3	Toluene

16. OTHER INFORMATION

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

End Of Document