

# 360 Panel Rocker Switches

Provides switching options for different configurations

Amperage Max. Operating	See table below
Single Pole Connections	0.187 in (4.80 mm) Quick Connect Tabs
Double Pole Connections	6.00 in (152.00 mm) Wire Leads

Part #	Pole/Throw	Image	Action	Amps Max. Operating			
				DC		AC	
				12V	24V	125V	250V
7480	SPST	1	OFF-ON	10A	10A	10A	10A
7481	SPST	1	OFF-(ON)	10A	10A	12A	6A
7482	SPDT	2	ON-OFF-ON	10A	8A	8A	8A
7483	SPDT	2	(ON)-OFF-ON	10A	8A	8A	8A
7484	SPDT	2	(ON)-OFF-(ON)	10A	8A	8A	8A
7485	SPDT	4	(ON)-OFF-(ON)	10A	8A	8A	8A
7490	DPST	1	OFF-ON	5A	5A	8A	4A
7491	DPDT	3	ON-ON	5A	5A	8A	4A
7492	DPDT	2	ON-OFF-ON	5A	5A	8A	4A
7493	DPDT	3	ON-(ON)	5A	5A	8A	4A
7494	DPDT	2	(ON)-OFF-ON	5A	5A	8A	4A
7495	DPDT	2	(ON)-OFF-(ON)	5A	5A	8A	4A

( ) = Momentary



## Recommended Panel Opening

PANEL THICKNESS	A	B
.030" (.76mm)-.050" (1.27mm)	.508" (12.90mm)	.756" (19.20mm)
.050" (1.27mm)-.078" (1.98mm)	.508" (12.90mm)	.764" (19.40mm)
.078" (1.98mm)-.125" (3.17mm)	.508" (12.90mm)	.780" (19.81mm)

+ .000 [.00] - .004 [.10]

