

# Gen-Sep™

The Gen-Sep™ is used in conjunction with a Vernalift muffler on generator sets. The water drain from the Gen-Sep™ can be located below the water line to eliminate irritating water splash during overnight moorings.

## GEN-SEP™

Part #	Application	A1 I/O		A2 DRAIN		H HEIGHT		J WIDTH		K DEPTH	
		INCHES	MM	INCHES	MM	INCHES	MM	INCHES	MM	INCHES	MM
1020150	Diesel	1.50	38	1.25	32	15.63	397	12.38	314	5.03	128
1020150P	Gasoline	1.50	38	1.25	32	15.63	397	12.38	314	5.03	128
1020162	Diesel	1.62	41	1.25	32	15.63	397	12.38	314	5.03	128
1020175	Diesel	1.75	44	1.50	38	15.63	397	12.38	314	5.03	128
1020200	Diesel	2.00	51	1.50	38	15.63	397	12.38	314	5.03	128
1020200P	Gasoline	2.00	51	1.50	38	15.63	397	12.38	314	5.03	128
1020250	Diesel	2.50	64	1.50	38	20.50	521	17.50	445	7.00	178
1020300	Diesel	3.00	76	1.50	38	20.50	521	17.50	445	7.00	178
1020350	Diesel	3.50	89	2.00	51	27.00	686	23.50	597	9.00	229
1020400	Diesel	4.00	102	2.50	64	27.00	686	23.50	597	9.00	229
1020450	Diesel	4.50	114	2.50	64	30.00	762	28.00	711	7.25	184
1020500	Diesel	5.00	127	3.00	76	30.00	762	28.00	711	7.25	184



