Material Safety Data Sheet

LANOCOTE®

I. PRODUCT IDENTIFICATION

Manufacturer: Forespar Products Corp.

Telephone: 949-858-8820

Address: 22322 Gilberto

Chemical Name: Lanolin Fatty Acids Rancho Santa Margarita, CA

Trade Name: Lanocote

92688

II. HAZARDOUS INGREDIENTS

Chemical Name CAS NUMBER

% Exposure Limit OSHA

Aliphatic Petroleum Distaillates

8052-41-3

17 100 ppm PEL

Lanolin

8006-54-0

83 ND

III. PHYSICAL DATA

Boiling Point:

NA

Evaporation Rate:

NA

Vapor Density(ai"=1); Solubility in Water:

Greater than 1

Vapor Pressure:

NA

Insoluble NA

Appearance:

Light Amber

Specific Gravity: Percent Volatile (Volume)

17

Odor:

Characteristic Odor

IV. FIRE AND EXPLOSION

Flash Point:

Flammable Limits:

408° F

NA

Extinguishing Media:

CO2, Dry Chemical Foam

Special Fire Fighting Procedures:

Wear self-contained breathing apparatus

Unusual Fire and Explosion Hazards:

None

V. HEALTH HAZARD / ROUTE(S) OF ENTRY

Threshold Limit Value

Aliphatic Petroleum Distaillates lowest TLV ACGIH 100 ppm

Symptoms of Overexposure

Inhalation (Breathing):

May cause anesthesia, headache dizziness, nausea and

upper respiratory irritation.

Skin Contact:

May cause irritation.

Eye Contact:

May cause irritation, te tearing and redness.

Ingestion (Swallowed): First Aid Emergency Procedures

May cause irritation, nausea, vomiting, and diarrhea.

Ingestion (Swallowed):

Eye Contact:

Do not induce vomiting, seek medical attention. Immediately flush eyes with large amounts of water.

Skin Contact: Inhalation (Breathing):

Wash with soap and water.

Remove to fresh air. Give artificial respiration if necessary. If

breathing is difficult, give oxygen.

Suspected Cancer Agent

Yes____ No_X

The components in this mixture have been found to be

noncarcinogenic by NTP, IARC and OSHA.

VI. REACTIVITY DATA

Conditions to avoid:

NA

Incompatibility:

Strong oxidizing materials

Hazardous decomposition products: Hazardous polymerization:

None

Will not occur: ___X___

VII. SPILL OR LEAK PROCEDURES

Spill Response Procedures

Leaking tubs or tubes should be placed in plastic bag or open pail until disposal. Lanocote becomes liquid above 90°F.

Waste Disposal Method

Cleanup with rags and combustible solvent. Liquid or grease should be burned in a chemical incinerator. Dispose of in accordance with local, state, and federal regulations.

VIII. SPECIAL HANDLING INFORMATION

Ventilation:

Sufficient to keep solvent vapor less than TLV.

Respiratory Protection:

Advised when concentrations exceed TLV.

Protective Gloves: Eye Protection:

Advised to prevent possible skin irritation.

Approved eye protection to safeguard against potential eye contact, irritation or injury.

Other Protective Equipment:

None required,

IX. SPECIAL PRECAUTIONS

Keep from sources of ignition. Avoid excessive inhalation of spray particles, do not take internally. Do not puncture, incinerate or store container above 120°F. Exposure to heat may cause bursting. Keep from children.

X. TRANSPORTATION DATA

Domestic Surface

Description:

Consumer Commodity

Hazard Class:

ORM-D

ID Number: Label Required:

None

Consumer Commodity (ORM-D)

Domestic Air

Description:

Consumer Commodity

Hazard Class:

ID Number:

ORM-D

Label Required:

None

Consumer Commodity ()ORM-D-AIR)

XI. REGULATORY INFORMATION

All ingredients for this product are listed on the TSCA Inventory.

SARA Title III chemicals:

None

California Prop 65 chemicals:

None None

CERCLA reportable quantity: RCRA hazardous waste number:

D001 (Ignitable)

Signature:

Title: President

Revision Date: March 16, 2005