

# **HARKEN®** MARINE GRIP

## **INSTALLATION INSTRUCTIONS:**

- 1) Dry and clean application surface and wipe with isopropyl alcohol.
- 2) If cutting from roll stock, cut to fit using a scissors or sharp blade.
- 3) Make sure the surface temperature is above 65° F (18° C) for adhesive to bond.
- 4) Peel off 3"- 4" of liner and press on to surface. Once that is secured, peel off the remainder of the liner and press firmly to the surface using a roller to smooth out bubbles. Marine Grip may be lifted and repositioned if necessary.

For best adhesion, allow MARINE GRIP to bond to the surface for 24 hours prior to use (maximum adhesion achieved after 72 hours).

HARKEN MARINE GRIP cleans easily with household or boat cleaners. Avoid contact with petroleum products. Always replace worn or damaged Marine Grip.

## **REMOVAL OF GRIP TAPE:**

- 1) Peel one corner while pulling toward the opposite corner.
- 2) Use a metal scraper or putty knife to slide under the tape as it is pulled back.

## **REMOVAL OF ADHESIVE:**

- 1) Apply an adhesive remover such as "Goof Off" or "Goo Gone" on the surface for one hour.
- 2) Use a metal scraper or putty knife to scrap off adhesive.
- 3) Wipe off any residue with a rag or paper towel.
- 4) Clean the surface with household cleaner or dishwashing detergent.
- 5) Rinse with fresh water.

GOO GONE is a trademark of Weiman Products, LLC.

**MADE IN USA** M1029 4/20

# **HARKEN®**

115W24983 Bluemound Road • Pewaukee, WI 53072 U.S.A.  
262.691.3320 • [www.harken.com](http://www.harken.com) • [harken@harken.com](mailto:harken@harken.com)