

# Reducing Solvent 2333N

## Thinners & Solvents

Thinners for Brushing Two-Part Polyurethanes or Epoxies



### PRODUCT DESCRIPTION

Reducing Solvent 2333N is a slow evaporating solvent for use in specific two-part polyurethane and epoxy products. Refer to the specific product directions for the amount to be used.

\* For use with most two-part polyurethanes and epoxy paints

### PRODUCT INFORMATION

Color	Y2333N
Specific Gravity	0.884
Volume Solids	0%
Typical Shelf Life	3 yrs
VOC (As Supplied)	884 g/lit
Unit Size	1 US Quart

### DRYING/OVERCOATING INFORMATION

#### Drying

#### Overcoating

#### Substrate Temperature

	41°F (5°C)		50°F (10°C)		73°F (23°C)		95°F (35°C)	
Overcoated By	Min	Max	Min	Max	Min	Max	Min	Max

### APPLICATION AND USE

Method	Refer to the specific product directions for the amount to be used.
Hints	Refer to the specific product directions for the amount to be used.
Compatibility/Substrates	For use with two-part polyurethanes and epoxy paints.

### TRANSPORTATION, STORAGE AND SAFETY INFORMATION

Storage	<b>TRANSPORTATION:</b> Reducing Solvent 2333N should be kept in securely closed containers during transport and storage. <b>STORAGE:</b> Exposure to air and extremes of temperature should be avoided. For the full shelf life of Reducing Solvent 2333N to be realized ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight.
---------	--

Safety	DISPOSAL: Container Disposal: Triple Rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by other procedures approved by state or local authorities. GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line.
--------	---

IMPORTANT NOTES	<i>The performance of any marine paint or coating depends on many factors outside the control of International Paint LLC., including surface preparation, proper application, and environmental conditions. Therefore, International Paint LLC. cannot guarantee this product's suitability for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND/OR MERCHANTABILITY ARE EXCEEDED. International Paint Inc. SHALL NOT, UNDER ANY CIRCUMSTANCES, BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase of this product, the buyer agrees that the sole exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint LLC. option.</i>
-----------------	--

Please refer to your local representative or visit <http://www.yachtpaint.com> for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2014.