

# LEWMAR®

## V700 Spares Instruction Leaflet


Part no: 66000600

Description: V700 Control Arm Kit


This Spares Kit contains the following:

- |   |   |                            |
|---|---|----------------------------|
| 1 | x | Control Arm                |
| 1 | x | Control Arm Screw          |
| 1 | x | Control Arm Torsion Spring |


Tools Required: 4 & 5mm Allen Keys.




1. Remove the two bolts using a 5mm Allen Key. Remove the Chain Pipe Cover.




2. Remove the Gypsy Drive Cap, anti-clockwise using the clutch operating lever. Remove the Drive washer.




3. Remove the Fleming retaining screw using a 4mm Allen key. Pull the Control Arm back to clear the Gypsy & remove the Gypsy Assembly.



4. Unscrew the Control Arm Shoulder Screw using a 5 mm Allen Wrench and remove screw. Remove the Control Arm and Torsion Spring from the base plate.



5. To reassemble Place the shoulder screw into the control arm and the torsion spring over the screw. Ensure that the elevated end of the spring sits into the control arm.



6. Place the control arm assembly into the hole ensuring that the arm is close to the shaft. Tighten the screw with a 5mm Allen key. Check that the control arm and spring operate correctly. Re-fit the gypsy and chain pipe cover by reversing the above procedure.