100% stainless steel exterior with 304 stainless steel diaphragm. 118 dB(A) rating. 24 volt, pre-wired, single trumpet horn with sealed sound unit. Built tough to withstand the harsh marine environment and backed by a 5 Year Warranty.

For a FREE catalog of Marinco Recreational Group products, contact your local dealer or Marinco



2655 Napa Valley Corporate Drive Napa, California 94558

Phone: 707-226-9600 Fax: 707-226-9670 Website: www.marinco.com

For more information and installation guides visit our website: www.marinco.com



Made in Thailand 20347 (3-01) Product No. 10017XL

## INSTALLATION AND WIRING INSTRUCTIONS

## INSTALLATION:

Select an installation position on the boat where a minimum of spray will hit the horn when the boat is underway.

At the same time, select an installation position which will assure the shortest possible length of wire from the horn to the power source.

Use the holes in the bracket as a template for the location of the mounting

points and drill holes for the bracket and wiring.

Insert wiring through the deck, then install the bracket to the deck surface Caulk all installation holes with silicone sealer. **Be sure the trumpet points slightly downward to permit water drainage.** 

## WIRING:

Connect wiring as illustrated in the diagram.

Cut wires of sufficient length to avoid any tension at the connecting points Use flexible stranded wire of sufficient size as per wiring chart.

If horn volume is weak, recheck wiring connections and ground wire.

Horn wiring has no polarity negative or positive can be attached to either wire.

If horn does not work at all, check the fuse.

## RECOMMENDED WIRE SIZES FOR 24 VOLT OPERATION

Wire Length\*\* Wire Size

0-100 feet 16 AWG\* over 100 feet 14 AWG

\* AWG: American Wire Gauge

\*\* As measured from the battery to the horn and back to the battery (round trip).

Wire Length\*\* Wire Size
0-30 meters 1.5 mm
over 30 meters 1.9 mm

