

Galvanized (Zinc-Plated) Steel		Diameter		L.T.		L.I.		H.T.		H.I.		O		E		R1		R2		T		Weight		Working Load Limit		Breaking Load	
Manufacturer Part Number	Model Number	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	g	oz	kg	lbs	kg	lbs
P-025-GS	MRPZ02.5	2.5	3/32"	20.0	0.79"	15.0	0.59"	40.0	1.57"	35.0	1.38"	7.0	0.28"	12.0	0.47"	3.50	0.14"	7.50	0.3"	3.5	0.14"	4	0.14	20	44	100	220
P-030-GS	MRPZ03.0	3.0	7/64"	23.5	0.93"	17.5	0.69"	45.5	1.79"	39.5	1.56"	8.5	0.33"	13.5	0.53"	4.25	0.17"	8.75	0.34"	4.0	0.16"	7	0.25	32	71	160	353
P-035-GS	MRPZ03.5	3.5	1/8"	27.5	1.08"	20.5	0.81"	52.5	2.07"	45.5	1.79"	10.0	0.39"	16.0	0.63"	5.00	0.2"	10.25	0.4"	5.0	0.2"	12	0.42	56	123	280	617
P-040-GS	MRPZ04.0	4.0	5/32"	32.0	1.26"	24.0	0.94"	61.0	2.4"	53.0	2.09"	11.5	0.45"	19.0	0.75"	5.75	0.23"	12.00	0.47"	6.0	0.24"	18	0.63	80	176	400	882
P-050-GS	MRPZ05.0	5.0	3/16"	37.0	1.46"	27.0	1.06"	70.5	2.78"	60.5	2.38"	13.0	0.51"	22.0	0.87"	6.50	0.26"	13.50	0.53"	7.0	0.28"	29	1.02	120	265	600	1323
P-060-GS	MRPZ06.0	6.0	1/4"	42.5	1.67"	30.5	1.2"	81.5	3.21"	69.5	2.74"	14.5	0.57"	25.0	0.98"	7.25	0.29"	15.50	0.61"	9.0	0.35"	49	1.73	200	441	1000	2205
P-070-GS	MRPZ07.0	7.0	9/32"	48.0	1.89"	34.0	1.34"	91.0	3.58"	77.0	3.03"	16.0	0.63"	28.0	1.1"	8.00	0.31"	17.00	0.67"	10.0	0.39"	71	2.5	320	705	1600	3527
P-080-GS	MRPZ08.0	8.0	5/16"	53.0	2.09"	37.0	1.46"	100.0	3.94"	84.0	3.31"	17.5	0.69"	31.5	1.24"	8.75	0.34"	18.50	0.73"	11.0	0.43"	105	3.7	480	1058	2400	5291
P-090-GS	MRPZ09.0	9.0	3/8"	58.0	2.28"	40.0	1.57"	108.0	4.25"	90.0	3.54"	19.0	0.75"	33.0	1.3"	9.50	0.37"	20.00	0.79"	12.0	0.47"	138	4.87	600	1323	3000	6614
P-100-GS	MRPZ10.0	10.0	7/16"	63.5	2.5"	43.5	1.71"	118.0	4.65"	98.0	3.86"	20.5	0.81"	36.0	1.42"	10.25	0.4"	21.75	0.86"	13.0	0.51"	183	6.46	720	1587	3600	7937
P-100-GS-PPE	MRPZ10.0 EN	10.0	7/16"	63.5	2.5"	43.5	1.71"	118.0	4.65"	98.0	3.86"	20.5	0.81"	36.0	1.42"	10.25	0.4"	21.75	0.86"	13.0	0.51"	183	6.46	-	-	3671	8093
P-120-GS	MRPZ12.0	12.0	1/2"	76.0	2.99"	52.0	2.05"	144.0	5.67"	120.0	4.72"	23.5	0.93"	43.0	1.69"	11.75	0.46"	26.00	1.02"	15.0	0.59"	321	11.32	880	1940	4400	9700
P-120-GS-PPE	MRPZ12.0 EN	12.0	1/2"	76.0	2.99"	52.0	2.05"	144.0	5.67"	120.0	4.72"	23.5	0.93"	43.0	1.69"	11.75	0.46"	26.00	1.02"	15.0	0.59"	321	11.32	-	-	4487	9892
P-140-GS	MRPZ14.0	14.0	9/16"	85.0	3.35"	57.0	2.24"	157.5	6.2"	129.5	5.1"	26.5	1.04"	49.0	1.93"	13.25	0.52"	28.50	1.12"	17.0	0.67"	479	16.9	1440	3175	7200	15873
P-160-GS	MRPZ16.0	16.0	5/8"	95.5	3.76"	63.5	2.5"	176.5	6.95"	144.5	5.69"	29.5	1.16"	54.0	2.13"	14.75	0.58"	31.75	1.25"	19.0	0.75"	717	25.29	2000	4409	10000	22046

Stainless Steel		Diameter		L.T.		L.I.		H.T.		H.I.		O		E		R1		R2		T		Weight		Working Load Limit		Breaking Load	
Manufacturer Part Number	Model Number	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	g	oz	kg	lbs	kg	lbs
P-025-SS	MRPI02.5	2.5	3/32"	20.0	0.79"	15.0	0.59"	40.0	1.57"	35.0	1.38"	7.0	0.28"	12.0	0.47"	3.50	0.14"	7.50	0.3"	3.5	0.14"	5	0.18	60	132	300	661
P-030-SS	MRPI03.0	3.0	7/64"	23.5	0.93"	17.5	0.69"	45.5	1.79"	39.5	1.56"	8.5	0.33"	13.5	0.53"	4.25	0.17"	8.75	0.34"	4.0	0.16"	8	0.28	100	220	500	1102
P-035-SS	MRPI03.5	3.5	1/8"	27.5	1.08"	20.5	0.81"	52.5	2.07"	45.5	1.79"	10.0	0.39"	16.0	0.63"	5.00	0.2"	10.25	0.4"	5.0	0.2"	12	0.42	130	287	650	1433
P-040-SS	MRPI04.0	4.0	5/32"	32.0	1.26"	24.0	0.94"	61.0	2.4"	53.0	2.09"	11.5	0.45"	19.0	0.75"	5.75	0.23"	12.00	0.47"	6.0	0.24"	18	0.63	170	375	850	1874
P-050-SS	MRPI05.0	5.0	3/16"	37.0	1.46"	27.0	1.06"	70.5	2.78"	60.5	2.38"	13.0	0.51"	22.0	0.87"	6.50	0.26"	13.50	0.53"	7.0	0.28"	30	1.06	270	595	1350	2976
P-060-SS	MRPI06.0	6.0	1/4"	42.5	1.67"	30.5	1.2"	81.5	3.21"	69.5	2.74"	14.5	0.57"	25.0	0.98"	7.25	0.29"	15.50	0.61"	9.0	0.35"	50	1.76	400	882	2000	4409
P-070-SS	MRPI07.0	7.0	9/32"	48.0	1.89"	34.0	1.34"	91.0	3.58"	77.0	3.03"	16.0	0.63"	28.0	1.1"	8.00	0.31"	17.00	0.67"	10.0	0.39"	73	2.57	550	1213	2750	6063
P-080-SS	MRPI08.0	8.0	5/16"	53.0	2.09"	37.0	1.46"	100.0	3.94"	84.0	3.31"	17.5	0.69"	31.5	1.24"	8.75	0.34"	18.50	0.73"	11.0	0.43"	108	3.81	660	1455	3300	7275
P-090-SS	MRPI09.0	9.0	3/8"	58.0	2.28"	40.0	1.57"	108.0	4.25"	90.0	3.54"	19.0	0.75"	33.0	1.3"	9.50	0.37"	20.00	0.79"	12.0	0.47"	142	5.01	840	1852	4200	9259
P-100-SS	MRPI10.0	10.0	7/16"	63.5	2.5"	43.5	1.71"	118.0	4.65"	98.0	3.86"	20.5	0.81"	36.0	1.42"	10.25	0.4"	21.75	0.86"	13.0	0.51"	187	6.6	1100	2425	5500	12125
P-120-SS	MRPI12.0	12.0	1/2"	76.0	2.99"	52.0	2.05"	144.0	5.67"	120.0	4.72"	23.5	0.93"	43.0	1.69"	11.75	0.46"	26.00	1.02"	15.0	0.59"	329	11.61	1500	3307	7500	16535
P-140-SS	MRPI14.0	14.0	9/16"	85.0	3.35"	57.0	2.24"	157.5	6.2"	129.5	5.1"	26.5	1.04"	49.0	1.93"	13.25	0.52"	28.50	1.12"	17.0	0.67"	492	17.35	2100	4630	10500	23149
P-160-SS	MRPI16.0	16.0	5/8"	95.5	3.76"	63.5	2.5"	176.5	6.95"	144.5	5.69"	29.5	1.16"	54.0	2.13"	14.75	0.58"	31.75	1.25"	19.0	0.75"	735	25.93	2700	5952	13500	29762

Aluminum Alloy (Zircal)		Diameter		L.T.		L.I.		H.T.		H.I.		O		E		R1		R2		T		Weight		Working Load Limit		Breaking Load	
Manufacturer Part Number	Model Number	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	g	oz	kg	lbs	kg	lbs
P-070-ZN	MRPZIC07.0	7.0	9/32"	48.0	1.89"	34.0	1.34"	91.0	3.58"	77.0	3.03"	16.0	0.63"	28.0	1.1"	8.00	0.31"	17.00	0.67"	10.0	0.39"	25	0.88	150	331	750	1653
P-100-ZN	MRPZIC10.0	10.0	7/16"	63.5	2.5"	43.5	1.71"	118.0	4.65"	98.0	3.86"	20.5	0.81"	36.0	1.42"	10.25	0.4"	21.75	0.86"	13.0	0.51"	65	2.29	300	661	1500	3307