

Galvanized (Zinc-Plated) Steel		Diameter		L.T.		L.I.		L.I.2		H.T.		H.I.		O		E		T		Weight		Working Load Limit		Breaking Load	
Manufacturer Part Number	Model Number	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	g	oz	kg	lbs	kg	lbs
S-025-GS	MRCZ02.5	2.5	3/32"	22.0	0.87"	10.0	0.39"	17.0	0.67"	27.0	1.06"	22.0	0.87"	3.5	0.14"	8.0	0.31"	3.5	0.14"	4	0.14	25	55	125	276
S-030-GS	MRCZ03.0	3.0	7/64"	24.0	0.94"	9.5	0.37"	18.0	0.71"	31.0	1.22"	25.0	0.98"	4.0	0.16"	9.0	0.35"	4.0	0.16"	6	0.21	40	88	200	441
S-035-GS	MRCZ03.5	3.5	1/8"	29.0	1.14"	12.0	0.47"	22.0	0.87"	35.0	1.38"	28.0	1.1"	5.0	0.2"	11.0	0.43"	5.0	0.2"	11	0.39	70	154	350	772
S-040-GS	MRCZ04.0	4.0	5/32"	33.0	1.3"	13.5	0.53"	25.0	0.98"	40.0	1.57"	32.0	1.26"	5.5	0.22"	12.5	0.49"	6.0	0.24"	15	0.53	100	220	500	1102
S-050-GS	MRCZ05.0	5.0	3/16"	38.0	1.5"	15.0	0.59"	28.0	1.1"	50.0	1.97"	40.0	1.57"	6.5	0.26"	16.0	0.63"	7.0	0.28"	26	0.92	150	331	750	1653
S-060-GS	MRCZ06.0	6.0	1/4"	43.0	1.69"	16.5	0.65"	31.0	1.22"	57.0	2.24"	45.0	1.77"	7.5	0.3"	19.0	0.75"	9.0	0.35"	43	1.52	250	551	1250	2756
S-070-GS	MRCZ07.0	7.0	9/32"	48.0	1.89"	18.0	0.71"	34.0	1.34"	66.0	2.6"	52.0	2.05"	8.5	0.33"	21.5	0.85"	10.0	0.39"	64	2.26	400	882	2000	4409
S-080-GS	MRCZ08.0	8.0	5/16"	53.0	2.09"	19.5	0.77"	37.0	1.46"	74.0	2.91"	58.0	2.28"	10.0	0.39"	24.0	0.94"	11.0	0.43"	87	3.07	550	1213	2750	6063
S-090-GS	MRCZ09.0	9.0	3/8"	58.0	2.28"	21.0	0.83"	40.0	1.57"	81.0	3.19"	63.0	2.48"	11.0	0.43"	26.0	1.02"	12.0	0.47"	129	4.55	700	1543	3500	7716
S-100-GS	MRCZ10.0	10.0	7/16"	63.0	2.48"	22.5	0.89"	43.0	1.69"	90.0	3.54"	70.0	2.76"	12.0	0.47"	29.0	1.14"	13.0	0.51"	166	5.86	900	1984	4500	9921
S-100-GS-PPE	MRCZ10.0 EN	10.0	7/16"	63.0	2.48"	22.5	0.89"	43.0	1.69"	90.0	3.54"	70.0	2.76"	12.0	0.47"	29.0	1.14"	13.0	0.51"	166	5.86	-	-	4589	10117
S-120-GS	MRCZ12.0	12.0	1/2"	74.0	2.91"	26.5	1.04"	50.0	1.97"	105.0	4.13"	81.0	3.19"	15.0	0.59"	33.0	1.3"	15.0	0.59"	278	9.81	1100	2425	5500	12125
S-140-GS	MRCZ14.0	14.0	9/16"	85.0	3.35"	30.5	1.2"	57.0	2.24"	121.0	4.76"	93.0	3.66"	17.0	0.67"	38.5	1.52"	17.0	0.67"	440	15.52	1800	3968	9000	19842
S-160-GS	MRCZ16.0	16.0	5/8"	96.0	3.78"	34.5	1.36"	64.0	2.52"	139.0	5.47"	107.0	4.21"	19.0	0.75"	45.0	1.77"	19.0	0.75"	614	21.66	2200	4850	11000	24251
S-180-GS	MRCZ18.0	18.0	11/16"	107.0	4.21"	38.5	1.52"	71.0	2.8"	158.0	6.22"	122.0	4.8"	23.0	0.91"	59.0	2.32"	22.0	0.87"	875	30.86	2600	5732	13000	28660

Stainless Steel		Diameter		L.T.		L.I.		L.I.2		H.T.		H.I.		O		E		T		Weight		Working Load Limit		Breaking Load	
Manufacturer Part Number	Model Number	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	g	oz	kg	lbs	kg	lbs
S-025-SS	MRCI02.5	2.5	3/32"	22.0	0.87"	10.0	0.39"	17.0	0.67"	26.0	1.02"	21.0	0.83"	3.5	0.14"	8.0	0.31"	3.5	0.14"	4	0.14	70	154	350	772
S-030-SS	MRCI03.0	3.0	7/64"	24.0	0.94"	9.5	0.37"	18.0	0.71"	31.0	1.22"	25.0	0.98"	4.0	0.16"	9.0	0.35"	4.0	0.16"	6	0.21	110	243	550	1213
S-035-SS	MRCI03.5	3.5	1/8"	29.0	1.14"	12.0	0.47"	22.0	0.87"	36.0	1.42"	29.0	1.14"	5.0	0.2"	11.0	0.43"	5.0	0.2"	11	0.39	150	331	750	1653
S-040-SS	MRCI04.0	4.0	5/32"	33.0	1.3"	13.5	0.53"	25.0	0.98"	41.0	1.61"	33.0	1.3"	5.5	0.22"	12.5	0.49"	6.0	0.24"	15	0.53	200	441	1000	2205
S-050-SS	MRCI05.0	5.0	3/16"	38.0	1.5"	15.0	0.59"	28.0	1.1"	50.0	1.97"	40.0	1.57"	6.5	0.26"	16.0	0.63"	7.0	0.28"	27	0.95	325	717	1625	3583
S-060-SS	MRCI06.0	6.0	1/4"	43.0	1.69"	16.5	0.65"	31.0	1.22"	57.0	2.24"	45.0	1.77"	7.5	0.3"	19.0	0.75"	9.0	0.35"	44	1.55	450	992	2250	4960
S-070-SS	MRCI07.0	7.0	9/32"	48.0	1.89"	18.0	0.71"	34.0	1.34"	66.0	2.6"	52.0	2.05"	8.5	0.33"	21.5	0.85"	10.0	0.39"	66	2.33	625	1378	3125	6889
S-080-SS	MRCI08.0	8.0	5/16"	53.0	2.09"	19.5	0.77"	37.0	1.46"	76.0	2.99"	60.0	2.36"	10.0	0.39"	24.0	0.94"	11.0	0.43"	90	3.17	770	1698	3850	8488
S-090-SS	MRCI09.0	9.0	3/8"	58.0	2.28"	21.0	0.83"	40.0	1.57"	83.0	3.27"	65.0	2.56"	11.0	0.43"	26.0	1.02"	12.0	0.47"	132	4.66	980	2161	4900	10803
S-100-SS	MRCI10.0	10.0	7/16"	63.0	2.48"	22.5	0.89"	43.0	1.69"	92.0	3.62"	72.0	2.83"	12.0	0.47"	29.0	1.14"	13.0	0.51"	171	6.03	1250	2756	6250	13779
S-120-SS	MRCI12.0	12.0	1/2"	74.0	2.91"	26.5	1.04"	50.0	1.97"	109.0	4.29"	85.0	3.35"	15.0	0.59"	33.0	1.3"	15.0	0.59"	285	10.05	1750	3858	8750	19290
S-140-SS	MRCI14.0	14.0	9/16"	85.0	3.35"	30.5	1.2"	57.0	2.24"	124.0	4.88"	96.0	3.78"	17.0	0.67"	38.5	1.52"	17.0	0.67"	451	15.91	2450	5401	12250	27007
S-160-SS	MRCI16.0	16.0	5/8"	96.0	3.78"	34.5	1.36"	64.0	2.52"	142.0	5.59"	110.0	4.33"	19.0	0.75"	45.0	1.77"	19.0	0.75"	700	24.69	3150	6945	15750	34723