

Revision Date 13-May-2020

SAFETY DATA SHEET

Version 4

1. IDENTIFICATION

Product identifier Product Name

VR-12A SUPER CLEAR VINYL SEALANT REPAIR KIT

Other means of identification Product Code

Recommended use of the chemical and restrictions on useRecommended UseSealantUses advised againstNo information available

81786

Details of the supplier of the safety data sheet Manufacturer Address ITW Permatex 6875 Parkland Blvd. Solon, Ohio 44139 USA Telephone: 1-87-Permatex (866) 732-9502 24-hour emergency phone number Chem-Tel: 800-255-3924 International Emergency: 00+1+ 813-248-0585 Contract Number: MIS0003453

E-mail address: mail@permatex.com

May Also Be Distributed by: ITW Permatex Canada 101-2360 Bristol Circle Oakville, ON Canada L6H 6M5 Telephone: (800) 924-6994

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| Serious eye damage/eye irritation | Category 2A |
|--|-------------|
| Carcinogenicity | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Flammable liquids | Category 2 |

Label elements

Emergency Overview

<u>Signal word</u> Danger

Causes serious eye irritation Suspected of causing cancer May cause respiratory irritation May cause drowsiness or dizziness Highly flammable liquid and vapor



Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Wear eye/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ ventilating/ lighting/ equipment Use non-sparking tools Take precautionary measures against static discharge Keep cool

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing In case of fire: Use CO2, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

May be harmful if swallowed.

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS No | Weight-% |
|-----------------|----------|----------|
| ACETONE | 67-64-1 | 30 - 60 |
| TETRAHYDROFURAN | 109-99-9 | 10 - 30 |

4. FIRST AID MEASURES

Description of first aid measures

| General advice | Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes. | | |
|--|--|--|--|
| Eye contact | In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes. | | |
| Skin contact | Wash skin with soap and water. | | |
| Inhalation | Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Administer oxygen if breathing is difficult. | | |
| Ingestion | IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician. | | |
| Self-protection of the first aider | Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. | | |
| Most important symptoms and effe | Most important symptoms and effects, both acute and delayed | | |
| Symptoms | See section 2 for more information. | | |
| Indication of any immediate medical attention and special treatment needed | | | |
| Note to physicians | Keep victim warm and quiet. | | |
| 5. FIRE-FIGHTING MEASURES | | | |

Suitable extinguishing media

Dry chemical, CO2, water spray or regular foam, Water spray, fog or regular foam, Use water spray or fog; do not use straight streams

Unsuitable extinguishing media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Those substances designated with a "P" may polymerize explosively when heated or involved in a fire. Runoff to sewer may create fire or explosion hazard. Substance may be transported hot.

Explosion data

| Sensitivity to | Mechanical Impact | None. |
|----------------|-------------------|-------|
| Sensitivity to | Static Discharge | None. |

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

| Personal precautions | ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do it without risk. |
|---------------------------|---|
| Other Information | Water spray may reduce vapor; but may not prevent ignition in closed spaces. |
| Environmental precautions | |

| Environmental precautions | Prevent entry into waterways, sewers, basements or confined areas. | | |
|--|--|--|--|
| Methods and material for containment and cleaning up | | | |
| Methods for containment | A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. | | |
| Methods for cleaning up | Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for later disposal. | | |
| Prevention of secondary hazards | Clean contaminated objects and areas thoroughly observing environmental regulations. | | |
| | 7. HANDLING AND STORAGE | | |
| Precautions for safe handling | | | |
| Advice on safe handling | Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required. | | |
| Conditions for safe storage, including any incompatibilities | | | |
| Storage Conditions | Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Store locked up. | | |
| Incompatible materials | Strong oxidizing agents, Acids, Reducing agents | | |
| 8. EXPOSURE CONTROLS/PERSONAL PROTECTION | | | |

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|-----------------|---------------|---|-----------------------------|
| ACETONE | STEL: 500 ppm | TWA: 1000 ppm | IDLH: 2500 ppm |
| 67-64-1 | TWA: 250 ppm | TWA: 2400 mg/m ³ | TWA: 250 ppm |
| | | (vacated) TWA: 750 ppm | TWA: 590 mg/m ³ |
| | | (vacated) TWA: 1800 mg/m ³ | - |
| | | (vacated) STEL: 2400 mg/m ³ | |
| | | The acetone STEL does not apply | |
| | | to the cellulose acetate fiber | |
| | | industry. It is in effect for all other | |
| | | sectors. | |
| | | (vacated) STEL: 1000 ppm | |
| TETRAHYDROFURAN | STEL: 100 ppm | TWA: 200 ppm | IDLH: 2000 ppm |
| 109-99-9 | TWA: 50 ppm | TWA: 590 mg/m ³ | TWA: 200 ppm |
| | S* | (vacated) TWA: 200 ppm | TWA: 590 mg/m ³ |
| | | (vacated) TWA: 590 mg/m ³ | STEL: 250 ppm |
| | | (vacated) STEL: 250 ppm | STEL: 735 mg/m ³ |
| | | (vacated) STEL: 735 mg/m ³ | |

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls

Showers Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

| Eye/face protection | Wear safety glasses with side shields (or goggles). |
|--------------------------------|--|
| Skin and body protection | Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves. |
| Respiratory protection | Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate. |
| General Hygiene Considerations | Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended. |

| 9. PHYSICAL AND CHEMICAL PROPERTIES | | | | |
|--|--|------------------|--|--|
| <u>9.1. Information on basic physica</u> Physical state Appearance Odor Odor threshold | Il and chemical properties Liquid Clear Pungent No information available | | | |
| Property | Values | Remarks • Method | | |
| pH | No information available | | | |
| Melting point / freezing point | No information available | | | |
| Boiling point / boiling range | 57 °C / 135 °F | | | |
| Flash point | -18 °C / 0 °F | Tag Closed Cup | | |
| Evaporation rate | No information available | 0 | | |
| Flammability (solid, gas) | No information available | | | |
| Flammability Limit in Air | | | | |
| Upper flammability limit: | No information available | | | |
| Lower flammability limit: | No information available | | | |
| Vapor pressure | No information available | | | |
| Vapor density | >1 | Air = 1 | | |
| Relative density | 0.94 | | | |
| Water solubility | Slightly soluble | | | |
| Solubility(ies) | No information available | | | |
| Partition coefficient | No information available | | | |
| Autoignition temperature | No information available | | | |
| Decomposition temperature | No information available | | | |
| Kinematic viscosity | No information available | | | |
| Dynamic viscosity | No information available | | | |
| Explosive properties | No information available | | | |
| Oxidizing properties | No information available | | | |
| Other Information | | | | |
| Other Information | No information available | | | |
| Softening point | No information available | | | |
| Molecular weight | 67.0154 | | | |
| VOC Content (%) Density | No information available | | | |
| Bulk density | No information available | | | |
| SADT (self-accelerating | No information available | | | |
| decomposition temperature) | | | | |
| accomposition temperature | | | | |

9. PHYSICAL AND CHEMICAL PROPERTIES

10. STABILITY AND REACTIVITY

Reactivity

No information available

<u>Chemical stability</u> Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents, Acids, Reducing agents

Hazardous Decomposition Products

Carbon oxides Hydrogen chloride Phosphorus

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

| Inhalation | Irritating to respiratory system. May cause drowsiness or dizziness. |
|--------------|--|
| Eye contact | Contact with eyes may cause irritation. May cause redness and tearing of the eyes. |
| Skin contact | May cause skin irritation and/or dermatitis. |
| Ingestion | Ingestion may cause irritation to mucous membranes. |

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|-----------------|--------------------|------------------------|------------------------|
| ACETONE | = 5800 mg/kg (Rat) | > 15700 mg/kg (Rabbit) | = 50100 mg/m³ (Rat)8 h |
| 67-64-1 | | | |
| TETRAHYDROFURAN | = 1650 mg/kg (Rat) | - | = 21000 ppm (Rat) 3 h |
| 109-99-9 | | | |

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| Sensitization Germ cell mutagenicity Carcinogenicity | No information available. No information available. The table below indicates whether each agency has listed any ingredient as a carcinogen. | | | |
|--|--|----------|-----|------|
| Chemical Name | ACGIH | IARC | NTP | OSHA |
| TETRAHYDROFURAN | A3 | Group 2B | - | Х |
| 109-99-9 | | | | |
| ACGIH (American Conference of Governmental Industrial Hygienists) A3 - Animal Carcinogen IARC (International Agency for Research on Cancer) Not classifiable as a human carcinogen Group 2B - Possibly Carcinogenic to Humans OSHA (Occupational Safety and Health Administration of the US Department of Labor) X - Present | | | | |
| Target Organ Effects | Central nervous system, Eyes, Respiratory system, Skin. | | | |
| The following values are calculated based on chapter 3.1 of the GHS document .ATEmix (oral)3415 mg/kgATEmix (dermal)29853 mg/kgATEmix (inhalation-dust/mist)169.9 mg/l | | | | |

12. ECOLOGICAL INFORMATION

Ecotoxicity

0.0185 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

<u>Mobility</u>

No information available.

| Chemical Name | Partition coefficient |
|-----------------------------|-----------------------|
| ACETONE 67-64-1 | -0.24 |
| TETRAHYDROFURAN 109-99-9 | 0.45 |

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

| Disposal of wastes | This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). |
|------------------------|---|
| Contaminated packaging | Do not reuse container. |
| US EPA Waste Number | D001, U002 U213 |

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name | California Hazardous Waste Status |
|-----------------|-----------------------------------|
| ACETONE | Ignitable |
| 67-64-1 | |
| TETRAHYDROFURAN | Toxic |
| 109-99-9 | Ignitable |

14. TRANSPORT INFORMATION

DOT

| UN/ID No Proper shipping name: Hazard Class Packing Group Emergency Response Guide Number | 1133 Adhesives, Limited Quantity (LQ) 3 II 128 |
|--|--|
| <u>IATA</u> UN/ID No Proper shipping name: Hazard Class ERG Code | ID 8000 Consumer commodity 9 9L |
| IMDG UN/ID No Proper shipping name: Hazard Class | 1133 Adhesives, Limited Quantity (LQ) 3 |

| Packing Group | II |
|---------------|----------|
| EmS-No | F-E, S-D |

| International Inventories | |
|---------------------------|----------------|
| TSCA | Complies |
| DSL/NDSL | Complies |
| EINECS/ELINCS | Not Listed |
| ENCS | Complies |
| IECSC | Complies |
| KECL | Complies |
| PICCS | Complies |
| AICS | Not determined |

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

| Acute health hazard | Yes |
|-----------------------------------|-----|
| Chronic Health Hazard | Yes |
| Fire hazard | Yes |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|-----------------|--------------------------|----------------|--------------------------|
| ACETONE | 5000 lb | - | RQ 5000 lb final RQ |
| 67-64-1 | | | RQ 2270 kg final RQ |
| TETRAHYDROFURAN | 1000 lb | - | RQ 1000 lb final RQ |
| 109-99-9 | | | RQ 454 kg final RQ |

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|-----------------|------------|---------------|--------------|
| ACETONE | Х | X | Х |
| 67-64-1 | | | |
| TETRAHYDROFURAN | Х | X | Х |
| 109-99-9 | | | |

| WATER | - | - | Х |
|-----------|---|---|---|
| 7732-18-5 | | | |

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

B2 - Flammable liquid, D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

| NFPA | Health ha |
|------|-----------|
| HMIS | Health ha |

Health hazards 2 Health hazards 2 Flammability 3 Flammability 3 Instability 0 Physical hazards 0

Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date

13-May-2020

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet