



Safety Data Sheet

1. Identification

Product Information.	8478900
Product Name:	Z*SPAR Splash Zone A-788 - 2-Part Epoxy Compound - Part B
Recommended Use.	Paints
Uses advised against.	Read label instructions and SDS
Supplier.	Kop-Coat, Inc. / Kop-Coat Marine Group 36 Pine Street Rockaway, NJ 07866 1-800-221-4466
Emergency telephone number.	Chemtrec: +1-800-424-9300 USA Chemtrec: +1 703-527-3887 ex-USA 24 hrs./day, 7 days/week

2. Hazards Identification

GHS Classification in accordance with 29 CFR 1910.1200

Carcinogenicity, category 2
Serious Eye Damage, category 1
Skin Irritation, category 2
Skin Sensitizer, category 1

GHS Pictograms



Signal Word

Danger

Unknown Acute Toxicity

68.0% of the mixture consists of ingredient(s) of unknown acute toxicity

HAZARD STATEMENTS

Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
Suspected of causing cancer.

Precautionary Statements - Prevention.

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Wash face and hands and any exposed skin thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response.

If on skin: Wash with plenty of water.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If exposed or concerned: Get medical advice/attention.

Immediately call a poison center/doctor.
 Specific treatment (If applicable, see label for any additional instructions).
 If skin irritation or rash occurs: Get medical advice/attention.
 Take off contaminated clothing and wash it before reuse.

Precautionary Statements - Storage.

Store locked up.

Precautionary Statements - Disposal.

Dispose of contents in accordance with local/regional/national/international regulations.

3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>
Crystalline silica (quartz)	14808-60-7	25-50
Talc	14807-96-6	10-25
MAGNESITE	546-93-0	10-25
TRIETHYLENETETRAMINE	112-24-3	2.5-10
2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL	90-72-2	2.5-10
Carbon black	1333-86-4	0.1-1.0

The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid Measures

Description of first-aid measures.

General advice.

Move victim to a safe isolated area. When symptoms persist or in all cases of doubt seek medical advice.
 Call a poison control center or doctor for treatment advice.

Inhalation.

Move to fresh air. Apply artificial respiration if victim is not breathing. Call a poison control center or doctor for treatment advice.

Skin contact.

Wash off immediately with soap and plenty of water. Remove all contaminated clothes and shoes. Remove and wash contaminated clothing before re-use. Call a poison control center or doctor for treatment advice.

Eye contact.

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Call a poison control center or doctor for treatment advice.

Ingestion.

Do not induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. If swallowed, call a poison control center or doctor immediately.

Symptoms.

See Section 2 and Section 11, Toxicological effects for description of potential symptoms.

Notes to physician.

Treat symptomatically.

5. Fire-fighting Measures

Extinguishing media.

Suitable extinguishing media.

Use: Dry powder. Alcohol-resistant foam. Carbon dioxide (CO₂).

Extinguishing media which shall not be used for safety reasons.

Water may be unsuitable for extinguishing fires.

Special hazards arising from the substance or mixture.

No information available.

Advice for firefighters.

Evacuate personnel to safe areas. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures.

Personal precautions.

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. All equipment used when handling the product must be grounded. Wear protective gloves/clothing and eye/face protection. Do not breathe vapors or spray mist. Avoid exceeding of the given occupational exposure limits (see section 8). Thoroughly decontaminate all protective equipment after use.

Advice for emergency responders.

Refer to protective measures listed in sections 7 and 8. Use personal protection recommended in Section 8.

Environmental precautions.

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological information.

Methods and materials for containment and cleaning up.

Methods for Containment.

Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Ground and bond containers when transferring material. Take precautionary measures against static discharges. Use personal protective equipment.

Methods for cleaning up.

Prevent further leakage or spillage if safe to do so. All equipment used when handling the product must be grounded. Ventilate the area. Use personal protective equipment as required. Clean contaminated objects and areas thoroughly while observing environmental regulations. Never return spills in original containers for re-use.

Reference to other sections.

See section 8 for more information.

7. Handling and Storage

Conditions for safe storage, including any incompatibilities.

Advice on safe handling.

Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. All equipment used when handling the product must be grounded. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Use according to package label instructions. Ground and bond containers when transferring material.

Hygiene measures.

Handle in accordance with good industrial hygiene and safety practice for diagnostics. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Storage Conditions.

Keep container closed when not in use. Keep in properly labeled containers. Keep containers tightly closed in a dry, cool and well-ventilated place. Store in accordance with local regulations. Keep from freezing. Keep away from food, drink and animal feedingstuffs.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Crystalline silica (quartz)	0.025 mg/m ³	N.E.	50 µg/m ³	N.E.
Talc	2 mg/m ³	N.E.	N.E.	N.E.
Carbon black	3 mg/m ³	N.E.	3.5 mg/m ³	N.E.

TLV = Threshold Limit Value TWA = Time Weighted Average PEL = Permissible Exposure Limit STEL = Short-Term Exposure Limit N.E. = Not Established

Engineering Measures.

Ensure adequate ventilation, especially in confined areas. Apply technical measures to comply with the occupational exposure limits.

Personal protective equipment.**Eye/Face Protection.**

If splashes are likely to occur, wear:. Safety glasses with side-shields. Tightly fitting safety goggles.

Skin and body protection.

Use:. Protective shoes or boots. Solvent-resistant gloves. Solvent-resistant apron and boots. Wear impervious gloves and/or clothing if needed to prevent contact with the material. Gloves must be inspected prior to use. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Remove and wash contaminated clothing before re-use.

Respiratory protection.

In case of inadequate ventilation wear respiratory protection. If exposure limits are exceeded or irritation is experienced, respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

9. Physical and chemical properties.**Information on basic physical and chemical properties.**

Physical state	Paste/Gel
Appearance	No Information
Color	Black
Odor	Amine
Odor Threshold	No Information
pH	No Information
Melting/freezing point., °C (°F)	No Information
Flash Point., °C (°F)	135 (275.00)
Boiling point/boiling range., °C (°F)	267 - 3,600 (512.6 - 6512)
Evaporation rate	No Information Available
Explosive properties.	No Information
Vapor pressure.	No Information
Vapor density.	No Information
Specific Gravity. (g/cm ³)	1.638
Water solubility.	No Information
Partition coefficient.	No Information
Autoignition temperature.,°C	No Information
Decomposition Temperature °C.	No Information
Viscosity, kinematic.	> 22 mm ² /s

Other information.

Volatile organic compounds (VOC) content.	0
Density, lb/gal	13.644

10. Stability and Reactivity**Reactivity.**

Stable under normal conditions.

Chemical stability.

Stable under recommended storage conditions.

Possibility of hazardous reactions.

None known based on information supplied.

Conditions to Avoid.

None known.

Incompatible Materials.

None known based on information supplied.

Hazardous Decomposition Products.

None known.

11. Toxicological Information**Information on toxicological effects.****Acute toxicity.****Product Information**

No Information

The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral) 10,115.9 mg/kg

ATEmix (dermal) 4,605.4 mg/kg

Component Information.

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>LD50 Oral</u>	<u>LD50 Dermal</u>	<u>LC50 Inhalation</u>
112-24-3	TRIETHYLENETETRAMINE	2500 mg/kg Rat	550 mg/kg Rabbit	N.I.
90-72-2	2,4,6-TRIS(DIMETHYLAMINOMETHYL) PHENOL	1200 mg/kg Rat	1280 mg/kg Rat	N.I.
1333-86-4	Carbon black	>15400 mg/kg Rat	N.I.	N.I.

N.I. = No Information

Skin corrosion/irritation.

No Information

Eye damage/irritation.

No Information

Respiratory or skin sensitization.

No Information

Ingestion.

No Information

Germ cell mutagenicity.

No Information

Carcinogenicity.

No Information

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>IARC</u>	<u>NTP</u>	<u>OSHA</u>
14808-60-7	Crystalline silica (quartz)	IARC Group 1	NTP Known Human Carcinogen	-
14807-96-6	Talc	IARC Group 3	-	-
1333-86-4	Carbon black	IARC Group 2B	-	-

Reproductive toxicity.

No Information

Specific target organ systemic toxicity (single exposure).

No Information

Specific target organ systemic toxicity (repeated exposure).

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard.

No Information

Primary Route(s) of Entry

No Information

12. Ecological Information

Toxicity.

43.13% of the mixture consists of ingredient(s) of unknown aquatic toxicity

Ecotoxicity effects.

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Talc 14807-96-6	-	LC50 96 h Brachydanio rerio >100 g/L	-
TRIETHYLENETETRAMINE 112-24-3	EC50 72 h Desmodesmus subspicatus 2.5 mg/L, EC50 72 h Pseudokirchneriella subcapitata 20 mg/L, EC50 96 h Pseudokirchneriella subcapitata 3.7 mg/L	LC50 96 h Poecilia reticulata 570 mg/L, LC50 96 h Pimephales promelas 495 mg/L	EC50 48 h Daphnia magna 31.1 mg/L

Persistence and degradability.

No data are available on the product itself.

Bioaccumulative potential.

Discharge into the environment must be avoided.

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>log POW</u>
112-24-3	TRIETHYLENETETRAMINE	-1.4

Mobility in soil.

No information

Other adverse effects.

No information

13. Disposal Considerations

Waste Disposal Guidance.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

<u>DOT</u>	No Information
<u>Additional Information:</u>	Not regulated. A liquid with a flashpoint above 200° F (93° C) is not regulated as a hazardous material.
<u>IMDG</u>	No Information
<u>Additional Information:</u>	Not regulated
<u>IATA</u>	No Information
<u>Additional Information:</u>	Not regulated

15. Regulatory Information

International Inventories:

TSCA	Complies
DSL	-
DSL/NDSL	-
EINECS/ELINCS	-
ENCS	-
IECSC	Complies
KECI	-
PICCS	Complies
AICS	-
NZIoC	Complies

TCSI

TSCA	United States Toxic Substances Control Act Section 8(b) Inventory.
DSL	Canadian Domestic Substances List.
DSL/NDSL	Canadian Domestic Substances List/Canadian Non-Domestic Substances List
EINECS/ELINCS	European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances.
ENCS	Japan Existing and New Chemical Substances.
IECSC	China Inventory of Existing Chemical Substances.
KECL	Korean Existing and Evaluated Chemical Substances.
PICCS	Philippines Inventory of Chemicals and Chemical Substances.
AICS	Australian Inventory of Chemical Substances.
NZIoC	New Zealand Inventory of Chemicals.
TCSI	Taiwan Chemical Substance Inventory

U.S. Federal Regulations:**SARA SECTION 313:**

This product does not contain any chemicals that are subject to the reporting requirements of SARA 313.

TOXIC SUBSTANCES CONTROL ACT 12(b):

This product does not contain any chemicals that are subject to the reporting requirements of TSCA 12(b).

ADDITIONAL INFORMATION

Additional Information - Sxn 15: No Information

CALIFORNIA PROPOSITION 65 CARCINOGENS**WARNING**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer.:

Chemical Name

Carbon black

CAS-No.

1333-86-4

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

No Proposition 65 Reproductive Toxins exist in this product.

NOTICE

Constituents of this product include crystalline silica which, if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

16. Other Information

Revision Date: 1/27/2022 **Supersedes Date:** 11/2/2021

Reason for revision: Revision Statement(s) Changed

Datasheet produced by: Regulatory Department

HMIS Ratings:

Health:	3*	Flammability:	1	Physical Hazard:	1	Personal Protection:	X
----------------	----	----------------------	---	-------------------------	---	-----------------------------	---

NFPA Ratings:

Health:	3	Flammability:	1	Instability:	1	Physical & Chemical:	---
----------------	---	----------------------	---	---------------------	---	---------------------------------	-----

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.