

# WIPER MOTOR | W50


## Installation Instructions

Before installation please read these instructions.



- 2 Speed, self-parking
- Heavy Duty motor, 50Nm
- Wipershaft in stainless steel
- Various sweep angle: 45 110°
- Dynamic park circiut
- Internal thermoswitch
- Insulated ground
- EMC protected
- Powers up to 1200mm/1200mm Arm/blade combinations

#### Instructions - Adjusting the sweep angle and parking position



### Changing the parking position.

Before the parking position is changed, the wiper motor should be in parked position (Default is set to left).

Keep battery main switch turned off during any operation inside of the wiper motor.


- Loosen the nut (1).
- Remove the bracket (2) and rotate it 180°.
- Assemble the bracket and tighten the nut firmly.

### Change of wiped angle.

The wiped angle can be set at any point between 45° and 110°. (Default is set to 45°).

Keep battery main switch turned off during any operation inside of the wiper motor.

- Loosen the ball/nut (3).
- Move the ball/nut to desired angle position and tighten it firmly.



Alt. 2 (Roca switch)

Switch
466221 / 12V
466222 / 24V

Actuator
466221 / 12V
466222 / 24V

G

Z speed / Parking


F

LED

Sw
F

G

G



#### Variations:

Max length:		Voltage input:	
L1	L2	12 V	24 V
28	78	531013	531014
53	103	531023	531024
78	128	531033	531034

Current diagram:	12 V	24 V
No load	< 6 A	< 3 A
Normal running	< 10 A	< 5A
Stall	< 40 A	< 20 A
Fuse	40 A	20 A

#### **Limited warranty**

- Roca warrants the wiper motors to be free from defective material and workmanship for a period of 3 years from the date of purchase.
- This warranty does not apply to failure or damage caused by improper installation, misuse, lightning strike or damage from a power surge.
- If failure occurs during this period, return it to your dealer for repair or replacement.

#### Wiper arms and blades:



Pantograph 536335 EP 538335 Black



Pantograph 536347 EP 538347 Black



Blade (28"- 40") 520828 - 40