

Series 15 Ball Bearing Utility Blocks



RF133
Suits loop head single blocks

RF613S
3mm (1/8") slotted pin, suits RF15100

- ✓ Smallest and lightest ball bearing block available.
- ✓ Precision moulded acetal sheave running on stainless steel ball bearings provides high performance and low friction.
- ✓ Single loop head blocks include an O-ring to separate running line from head lashing or fixing.
- ✓ RF15151 cheek block features lateral supports for improved mounting stability.

- ✓ RF15174 pivoting lead block has 4-point fastening for load distribution and low profile. Can be mounted without disassembly.
- ✓ RF15711 exit block has a formed single piece housing for maximum strength and minimal rope wear.
- ✓ RF15711 exit block has a flush rivet to minimise cutout dimensions and facilitate installation.

- ⬆ Dinghy control lines.
- ⬆ Vangs, cunninghams and tweakers.
- ⬆ Shock cord tensioning systems.
- ⊖ Sheaves: UV stabilised acetal.
- ⊖ Ball bearings: Stainless steel.
- ⊖ Cheeks & head fittings: Grade 316 stainless steel.

PRODUCT No.	DESCRIPTION	SHEAVE	MAX.	MAX.	PIN	M.W.L.	B.L.	WEIGHT	SHEAVE	MAX.	MAX.	PIN	M.W.L.	B.L.	WEIGHT
		DIAM.	ROPE	WIRE	DIAM.	kg	kg	g	DIAM.	ROPE	WIRE	DIAM.	lb	lb	oz
		mm	mm	mm	mm				in.	in.	in.	in.	lb	lb	oz
BB RF15100	Single block, swivel shackle head	15	5	-	3	120	400	11	5/8	3/16	-	1/8	260	880	0.7
RF15101	Single block, loop head	15	5	-	-	120	550	7	5/8	3/16	-	-	260	1210	0.3
RF15111	Single block, becket, loop head	15	5	-	-	120	550	9	5/8	3/16	-	-	260	1210	0.3
RF15141	Stand-up block	15	5	-	-	120	550	10	5/8	3/16	-	-	260	1210	0.4
RF15151	Cheek block	15	5	-	-	120	550	9	5/8	3/16	-	-	260	1210	0.3
RF15171	Upright lead block	15	5	-	-	120	550	9	5/8	3/16	-	-	260	1210	0.3
RF15174	Pivoting lead block	15	5	-	-	120	350	16	5/8	3/16	-	-	260	770	0.6
RF15180	Single block, swivel hook head	15	5	-	-	100	200	13	5/8	3/16	-	-	220	440	0.4
RF15202	Double block, loop head	15	5	-	-	240	700	23	5/8	3/16	-	-	530	1540	0.8
RF15212	Double block, becket, loop head	15	5	-	-	240	700	24	5/8	3/16	-	-	530	1540	0.9
RF15302	Triple block, loop head	15	5	-	-	360	850	28	5/8	3/16	-	-	790	1870	1.0
RF15312	Triple block, becket, loop head	15	5	-	-	360	850	30	5/8	3/16	-	-	790	1870	1.0
RF15711	Exit block	15	5	-	-	120	550	14	5/8	3/16	-	-	260	1210	0.5
RF133	Saddle, 9mm (3/8") internal clearance, suits 2 x 4mm (3/16") fasteners at 27mm (1 1/16") centres	-	-	-	-	-	-	2	-	-	-	-	-	-	0.1
RF613S	Shackle, slotted pin, suits RF15100	-	-	-	3	-	-	3	-	-	-	1/8	-	-	0.1
RF633S	Shackle, suits double & triple blocks	-	-	-	4	-	-	5	-	-	-	5/32	-	-	0.2
RF1851	Shackle, suits single loop head blocks	-	-	-	3	-	-	2	-	-	-	1/8	-	-	0.1