



ACR-160



Automatic Charge Separator

Model
ACR-160
160 Amp

Design Features

- Microprocessor controlled, dual sensing
- Starter battery priority
- Easy to install - does not require changing the existing circuit or the alternator
- Potted, waterproof, sealed unit
- Low standby current
- Automatic detection of 12 or 24 VDC systems
- 160 Amp continuous rated, 480 Amp peak (250 msec)
- Monitoring of relay activation by external LED
- Over-voltage protection

2 YEAR LIMITED WARRANTY

MODEL NO. ACR-160		
ELECTRICAL SPECIFICATIONS	OPERATING VOLTAGE	12 VDC / 24 VDC (Automatic detection)
	MAXIMUM CURRENT	160A
	PEAK CURRENT	480A for 250 milliseconds
	CONSUMPTION OFF	12V = 1.8mA / 24V = 2.0mA
	CONSUMPTION ON	12V = 340mA / 24V = 170mA
	MINIMUM CHARGE TIME	60 seconds
	FAST OPENING	< 11.8V (12V) / 23.6 (24V) after 4 seconds
	EXTERNAL FUSE FOR BATTERY CONNECTIONS	200A, 32V
MINIMUM SIZE OF WIRES FOR BATTERY CONNECTION		
CONNECTIONS	A1 (Stud & Nut, M8)	Connects to Positive terminal of Starter Battery
	A2 (Stud & Nut, M8)	<ul style="list-style-type: none"> - Connects to Positive of Auxiliary Battery in normal function - Connects to Positive of Load in "Voltage Dependent Switch" function
	STATUS (6.3 mm / 1/4" Quick Disconnect / FASTON connector)	<ul style="list-style-type: none"> - When connected to Positive terminal of Starter Battery in "Start Assistance" function, the relay is energized - No connection - normal operation - When connected to battery Negative through switch, the relay is de-energized
	MINUS (6.3 mm / 1/4" Quick Disconnect / FASTON connector)	Connects to Starter Battery Negative
	LED (6.3 mm / 1/4" Quick Disconnect / FASTON connector)	When connected to external LED, will indicate relay energization
DISPLAY	LED (OPTIONAL)	Will indicate relay energized (ON)
INGRESS PROTECTION		
COMPLIANCE	EMC COMPLIANCE	EN61000-6-2: 2005: Immunity Against Industrial Environment . EN6100-6-3: 2007: Conducted and Radiated Emissions for Residential, Commercial and Light Industrial Environment. 2004/104/EC: Automotive Directive.
	OPERATING TEMPERATURE RANGE	-20°C to 40°C (Linearly de-rate to 80A at 85°C) -4°F to 104°F (Linearly de-rate to 80A at 185°F)
DIMENSIONS	(L X W X H), MM	106.4 x 73 x 57.2
	(L X W X H), INCHES	4.2 x 2.9 x 2.3
WEIGHT	KG	0.46
	LB	1.0

NOTE: Specifications are subject to change without notice

12004-ACR-160-0725