

tuff luff : specification Charts

1205 | 1706 | 2206 | 3007 | 4807 | 6008 | 7608 | TL-1003 | TL-1004



1205

Complete Kit	1205-25	1205-30	1205-36	1205-46
Extrusion Only	1205-12-EXT	1205-30-EXT	1205-36-EXT	1205-46-EXT
Extrusion Length	25' (7.6m)	30' (9m)	36' (11m)	46' (14m)
Max Head Stay Length	29' (8.8m)	34' (10.2m)	40' (12.2m)	50' (15.2)
Max Wire	Standard 1/4" Metric 6mm	Standard 1/4" Metric 6mm	Standard 1/4" Metric 6mm	Standard 1/4" Metric 6mm
Max Rod	-10	-10	-10	-10
Luff Tape	#5 (4mm) .159" OD	#5 (4mm) .159" OD	#5 (4mm) .159" OD	#5 (4mm) .159" OD
Extrusion Weight*	0.11 Lbs./ ft 0.16 Kg/M	0.11 Lbs./ ft 0.16 Kg/M	0.11 Lbs./ ft 0.16 Kg/M	0.11 Lbs./ ft 0.16 Kg/M
Kevlar Bumper (optional)	1205-10	1205-10	1205-10	1205-10
Top Cap	1205-13	1205-13	1205-13	1205-13
Feeder	1205-02	1205-02	1205-02	1205-02
Spacer Tube	1205-03 44"	1205-03 44"	1205-03 44"	1205-03 44"
Dimensional Weight*	19 Lbs. (8.6kg)	19 Lbs. (8.6kg)	19 Lbs. (8.6kg)	19 Lbs. (8.6kg)
Shipping Weight	6 Lbs. (2.72kg)	7 Lbs. (3.18kg)	8 Lbs. (3.63kg)	10 Lbs. (4.54kg)

[top](#)



1706

Complete Kit	1706-36	1706-46	1706-59
Extrusion Only	1706-36-EXT	1706-46-EXT	1706-59-EXT
Extrusion Length	36' (11m)	46' (14m)	59' (18m)
Max Head Stay Length	40' (12.2m)	50' (15.2m)	63' (19.2m)
Max Wire	Standard 5/16" Metric 8mm	Standard 5/16" Metric 8mm	Standard 5/16" Metric 8mm
Max Rod	-17	-17	-17
Luff Tape	#6 (5mm) .197" OD	#6 (5mm) .197" OD	#6 (5mm) .197" OD
Extrusion Weight*	0.17 Lbs./ ft 0.25 Kg/M	0.17 Lbs./ ft 0.25 Kg/M	0.17 Lbs./ ft 0.25 Kg/M
Kevlar Bumper (optional)	1706-10	1706-10	1706-10
Top Cap	1706-13	1706-13	1706-13
Feeder	1706-02	1706-02	1706-02
Spacer Tube	2206-03 44"	2206-03 44"	2206-03 44"

Dimensional Weight*	19 Lbs. (8.6kg)	19 Lbs. (8.6kg)	19 Lbs. (8.6kg)
Shipping Weight	9 Lbs. (4.08kg)	12 Lbs. (5.44kg)	13 Lbs. (5.9kg)

*Dimensional weights are for shipping purposes only. They do not reflect the actual system weight.

All 1205, 1706, and 2206 systems may be shipped UPS or FedEx.

All 3007, 4807, 6008, 7608, TL-1003, TL-1004 must be shipped by truck.

[top](#)



2206

Complete Kit	2206-46	2206-59	2206-72
Extrusion Only	2206-46-EXT	2206-59-EXT	2206-72-EXT
Extrusion Length	46' (14m)	59' (18m)	72' (22m)
Max Head Stay Length	50' (15.2m)	63' (19.2m)	76' (23.2m)
Max Wire	Standard 3/8" Metric 10mm	Standard 3/8" Metric 10mm	Standard 3/8" Metric 10mm
Max Rod	-22	-22	-22
Luff Tape	#6 (5mm) .197" OD	#6 (5mm) .197" OD	#6 (5mm) .197" OD
Extrusion Weight*	0.24 Lbs./ft 0.36 Kg/M	0.24 Lbs./ft 0.36 Kg/M	0.24 Lbs./ft 0.36 Kg/M
Kevlar Bumper (optional)	2206-10	2206-10	2206-10
Top Cap	2206-13	2206-13	2206-13
Feeder	2206-02	2206-02	2206-02
Spacer Tube	2206-03 44"	2206-03 44"	2206-03 44"
Dimensional Weight*	23 Lbs. (10.5kg)	23 Lbs. (10.5kg)	23 Lbs. (10.5kg)
Shipping Weight	15 Lbs. (6.8kg)	18 Lbs. (8.16kg)	23 Lbs. (10.43kg)

*Dimensional weights are for shipping purposes only. They do not reflect the actual system weight.

All 1205, 1706, and 2206 systems may be shipped UPS or FedEx.

All 3007, 4807, 6008, 7608, TL-1003, TL-1004 must be shipped by truck.

[top](#)



3007

Complete Kit	3007-80
Extrusion Only	3007-80-EXT
Extrusion Length	80' (24.3m)
Max Head Stay Length	86' (26.1m)
Max Wire	Standard 7/16" (Metric 11mm)
Max Rod	-30
Luff Tape	#7 (6mm) .236" OD
Extrusion Weight*	0.30 Lbs./ft (0.45 Kg/M)

Kevlar Bumper (optional)	3007-10
Top Cap	3007-13
Feeder	3007-02
Spacer Tube	3007-03 60 "
Dimensional Weight*	104 Lbs. (47.2kg)
Shipping Weight	40 Lbs. (18.14kg)

*Dimensional weights are for shipping purposes only. They do not reflect the actual system weight.

All 1205, 1706, and 2206 systems may be shipped UPS or FedEx.

All 3007, 4807, 6008, 7608, TL-1003, TL-1004 must be shipped by truck.

[top](#)

1"
25.4mm



4807

Complete Kit	4807-95
Extrusion Only	4807-95-EXT
Extrusion Length	95' (28.9m)
Max Head Stay Length	101' (30.7m)
Max Wire	Standard 9/16" (Metric 14mm)
Max Rod	-48
Luff Tape	#7 (6mm) .236" OD
Extrusion Weight*	0.41 Lbs./ ft (0.62 Kg/M)
Kevlar Bumper (optional)	4807-10
Top Cap	4807-13
Feeder	4807-02
Spacer Tube	4807-03 72"
Dimensional Weight*	104 Lbs. (47.2kg)
Shipping Weight	55 Lbs. (24.95kg)

*Dimensional weights are for shipping purposes only. They do not reflect the actual system weight.

All 1205, 1706, and 2206 systems may be shipped UPS or FedEx.

All 3007, 4807, 6008, 7608, TL-1003, TL-1004 must be shipped by truck.

[top](#)

1"
25.4mm



6008

Complete Kit	6008-110
Extrusion Only	6008-110-EXT
Extrusion Length	110' (33.5m)
Max Head Stay Length	116' (33.5m)
Max Wire	Standard 5/8" (Metric 16mm)
Max Rod	-60
Luff Tape	#8 (7mm) .275" OD
Extrusion Weight*	0.46 Lbs./ ft (0.69 Kg/M)


Kevlar Bumper (optional)	6008-10
Top Cap	6008-13
Feeder	6008-02
Spacer Tube	6008-03 72"
Dimensional Weight*	104 Lbs. (47.2kg)
Shipping Weight	70 Lbs. (31.75kg)

*Dimensional weights are for shipping purposes only. They do not reflect the actual system weight.

All 1205, 1706, and 2206 systems may be shipped UPS or FedEx.

All 3007, 4807, 6008, 7608, TL-1003, TL-1004 must be shipped by truck.

[top](#)



7608

Complete Kit	7608-130
Extrusion Only	7608-130-EXT
Extrusion Length	130' (39.6m)
Max Head Stay Length	136' (40.8m)
Max Wire	Standard 5/8" (Metric 16mm)
Max Rod	-76
Luff Tape	#8 (7mm) (.275" OD)
Extrusion Weight*	0.51 Lbs./ ft (0.77 Kg/M)
Kevlar Bumper	N/A
Top Cap	N/A
Feeder	7608-02
Spacer Tube	7608-03 72"
Dimensional Weight*	104 Lbs. (47.2kg)
Shipping Weight	140Lbs. (63.5kg)

*Dimensional weights are for shipping purposes only. They do not reflect the actual system weight.

All 1205, 1706, and 2206 systems may be shipped UPS or FedEx.

All 3007, 4807, 6008, 7608, TL-1003, TL-1004 must be shipped by truck.

[top](#)



TL-1003

Complete Kit	TL-1003
Extrusion Only	TL-1003-EXT
Extrusion Length	95' (29.9m)
Max Head Stay Length	101' (30.7m)
Max Wire	Standard 5/8" (Metric 16mm)
Max Rod	-60
Luff Tape	#7 (6mm) .236" OD
Extrusion Weight*	0.27 Lbs./ ft (0.41 Kg/M)

Kevlar Bumper	N/A
Top Cap	N/A
Feeder	TL-1003-02
Spacer Tube	TL-1003-72"
Dimensional Weight*	104 Lbs. (47.2kg)
Shipping Weight	40 Lbs. (18.2kg)

*Dimensional weights are for shipping purposes only. They do not reflect the actual system weight.

All 1205, 1706, and 2206 systems may be shipped UPS or FedEx.

All 3007, 4807, 6008, 7608, TL-1003, TL-1004 must be shipped by truck.

[top](#)



TL-1004

Complete Kit	TL-1004
Extrusion Only	TL-1004-EXT
Extrusion Length	85' (25.9m)
Max Head Stay Length	91' (27.7m)
Max Wire	Standard 5/8" (Metric 16mm)
Max Rod	-53
Luff Tape	#6 (5mm) .197" OD
Extrusion Weight*	0.17 Lbs./ ft (0.25 Kg/M)
Kevlar Bumper	N/A
Top Cap	N/A
Feeder	TL-1004-02
Spacer Tube	6008-03 72"
Dimensional Weight*	104 Lbs. (47.2kg)
Shipping Weight	32 Lbs. (14.5kg)

*Dimensional weights are for shipping purposes only. They do not reflect the actual system weight.

All 1205, 1706, and 2206 systems may be shipped UPS or FedEx.

All 3007, 4807, 6008, 7608, TL-1003, TL-1004 must be shipped by truck.

[top](#)