

DP 380



GENERAL PURPOSE GRADE DOUBLE-COATED POLYESTER FILM TAPE

TYPICAL APPLICATIONS

- For mounting banners, light signs, window blinds, emblems and nameplates
- Also used for long-term or permanent bonding and attachment applications, including POP displays and laminating materials

PRODUCT FEATURES

- Excellent adhesion and shear
- Excellent conformability to most irregular surfaces
- Superior moisture resistance in high humidity environments
- Converter-friendly

CONSTRUCTION

Overall Grade/Function: General
Backing: Polyester (PET) film
Adhesive: Solvent-based acrylic
Liner: Glassine

STANDARD WIDTH(S)

0.47 in 0.74 in 0.94 in 1.88 in

STANDARD LENGTH(S)

50 m

Contact your Shurtape sales representative for other available sizes

STANDARD CORE SIZE

3 in

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	14.3 lbs/in width	25.0 N/10 mm
Adhesion to Stainless Steel	60 oz/in width	6.57 N/10 mm
Thickness (with liner)	6.8 mils	0.17 mm
Thickness (without liner)	4.4 mils	0.11 mm
Elongation	120%	120%
Maximum Service Temperature	257 F	125 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

