

PC 769



by **Shurtape®**

PROFESSIONAL GRADE, CLEAN REMOVAL DUCT TAPE

TYPICAL APPLICATIONS

- Offers aggressive adhesion without leaving residue behind for up to 6 months, making it ideal for use in for a variety of indoor and outdoor projects such as holding cords, bundling and repair projects

PRODUCT FEATURES

- Clean removal up to 6 months on most outdoor and indoor surfaces
- Aggressive adhesive waterproof backing
- Easy to unwind and tear
- UV resistant
- Made using Polybonded CO-EX Technology®

CONSTRUCTION

Overall Grade/Function: Professional
Backing: Waterproof polyethylene film with a cloth carrier
Adhesive: Natural rubber

STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

APPLICABLE STANDARDS

None

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

STANDARD

METRIC

Tensile Strength	30 lbs/in width	52.5 N/10 mm
Adhesion to Stainless Steel	55 oz/in width	6.02 N/10 mm
Thickness (nominal)	12 mils	0.31 mm
Elongation	24%	24%
Service Temperature Range	50 F to 200 F	10 C to 93.3 C

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

