

PE 900



9.0 MIL UV-RESISTANT MARINE HEAT SHRINK TAPE

TYPICAL APPLICATIONS

- Used for marine shrink applications and vapor barrier seaming in boat storage and transportation applications
- Also used for patching, repairing, bundling, wrapping and sealing applications across a variety of surfaces

PRODUCT FEATURES

- Excellent conformability and flexibility
- Maintains a watertight seal and humidity resistance in all weather and climate conditions
- Available with serrated or straight edge

CONSTRUCTION

Overall Grade/Function: UV-resistant

Backing: Polyethylene film

Adhesive: Synthetic rubber

STANDARD WIDTH(S)

48 mm 72 mm 96 mm 144 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

UL 723; ASTM e84

COLOR(S)



BLUE
(BLU)



WHITE
(WHI)

PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	22 lbs/in width	38.5 N/10 mm
Adhesion to Stainless Steel	85 oz/in width	9.3 N/10 mm
Thickness	9 mils	0.23 mm
Elongation	100%	100%
Service Temperature Range	14 F to 158 F	-10 C to 70 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment.

Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

