# Form# TDS-T-Rex Extreme Tread Tape-07/03/2023 MMC 00792 1-REX® and Shurtape® are registered trademarks of Shurtape Technologies, LLC

# **Extreme Tread Tape**





### TYPICAL APPLICATIONS

• For improving surface traction on a variety of surfaces, such as steps, walkways, trailers and more to help prevent slips and accidents

### PRODUCT FEATURES

- Extreme industrial quality tape made with a multi-layer grit embedding process for long-lasting wear
- Helps improve surface traction on ladders, steps and walkways
- UV and weather-resistant
- Stronger adhesive bond than standard anti-slip tapes
- Meets and exceeds OSHA federal recommendations

## CONSTRUCTION

Overall grade/function: Super-Tough Backing: Polymer emulsion Adhesive: Solvent rubber emulsion

## STANDARD WIDTH(S)

2 in

## STANDARD LENGTH(S)

8 in

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free

### COLOR(S)



### PHYSICAL PROPERTIES **STANDARD METRIC**

Adhesion to Steel 144 oz/in 16.1 N/10mm **Thickness** 110 mil 2.8 mm -40 C to 104 C Service Temperature Range -40 F to 220 F

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



