



TECHNICAL DATA SHEET SUPER LUBE® SILICONE AEROSOL

March 2024

PRODUCT DESCRIPTION:

Super Lube® Silicone Aerosol is a general-purpose liquid aerosol lubricant, primarily designed to reduce friction in non-load bearing mechanical assemblies.

Super Lube® Silicone Aerosol is safe to use on rubber. Caution should be exercised when applying the spray to plastic or finished surfaces, as this product may negatively affect painted or lacquered finishes.

The silicone base has high dielectric capabilities and protects well against rust and corrosion.

Super Lube® Silicone Aerosol is NSF Food Grade rated H1 for incidental food contact. Meets former USDA (H1) guidelines.



FEATURES:

- ❖ Corrosion inhibitor
- ❖ Long lasting
- ❖ Safe to use on rubber, vinyl and plastic
- ❖ Dielectric
- ❖ Prevents freezing
- ❖ Extreme temperature use
- ❖ Prevents doors, locks and windows from binding and squeaking
- ❖ Kosher certified
- ❖ NSF Registered H1, # 136589

TYPICAL APPLICATIONS:

- ❖ O-rings, rubber gaskets and grommets
- ❖ Doors, locks and windows
- ❖ Food manufacturing equipment
- ❖ Tools
- ❖ Mold release
- ❖ High speed machinery
- ❖ Electronic equipment
- ❖ Weather stripping
- ❖ Treadmills
- ❖ Exercise equipment

PACKAGE SIZES:

Part No.	Description
91110	11 oz Aerosol



TECHNICAL DATA SHEET SUPER LUBE® SILICONE AEROSOL

March 2024

PROPERTIES:

Test	Test Method	Rating
Color:		Translucent clear
Temperature Range:		-40°F to 392°F (-40°C to 200°C)
Odor:		Solvent-like
Type of film:		Non-drying
Specific gravity:		.965
Solvent content VOC (California):		<60%

DIRECTIONS:

- Use in a well-ventilated area.
- Shake can prior and during use.
- Wipe clean the area to be sprayed.
- Hold can approximately 8" from intended area.
- Use handy extension tube for pinpoint applications.

SHELF LIFE / WARRANTY:

Super Lube® products have a five (5) year recommended shelf life when stored in the original container and in reasonable ambient conditions. The warranty period is twenty-four (24) months from the date of purchase. For complete information visit www.super-lube.com/what-is-the-shelf-life-ezp-320.html.



See Safety Data Sheet (SDS) for further details regarding safe use of this product.



The information provided in this Technical Data Sheet, including the recommendations for use and application of the product are based on our knowledge and experience of the product as of the date of this data sheet. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Kano Laboratories LLC is, therefore not liable for the suitability of our product for the production processes and conditions in respect for which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

All Super Lube® trademarks in this document are trademarks of Kano Laboratories LLC.