

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 6/2/2022

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : T-Greaser®

1.2. Recommended use and restrictions on use

Recommended use : Can be diluted 1:100 to 1:1. T-Greaser® should be used as a multi-purpose cleaner, Use

according to manufacturer's directions.

Restrictions on use : None known

1.3. Supplier

Supplier

Trac Ecological

3400 SW 26th Terrace, Unit A03

Dania Beach, FL 33312

USA

T (954) 987-2722

info@trac-online.com - www.trac-online.com

1.4. Emergency telephone number

Emergency number : +1-800-255-3924

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Corrosive to metals Category 1 H290 May be corrosive to metals

Skin corrosion/irritation Category 1B H314 Causes severe skin burns and eye damage

Serious eye damage Category 1 H318 Causes serious eye damage

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H290 - May be corrosive to metals

H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS US) : P234 - Keep only in original container.

P260 - Do not breathe mist, vapors.

P264 - Wash hands, forearms and face thoroughly after handling.

P280 - Wear eye protection, protective gloves, protective clothing, face protection.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor/physician.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P310 - Immediately call a POISON CENTER or doctor/physician.

P363 - Wash contaminated clothing before reuse.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P310 - Immediately call a POISON CENTER or doctor/physician.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P310 - Immediately call a POISON CENTER or doctor/physician.

P390 - Absorb spillage to prevent material-damage.

P405 - Store locked up.

P406 - Store in corrosive resistant container with a resistant inner liner.

 $\ensuremath{\mathsf{P501}}$ - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Sodium Metasilicate Pentahydrate	CAS-No.: 10213-79-3	1 - 10
Sodium xylenesulfonate	CAS-No.: 1300-72-7	1 – 5
Tetrapotassium pyrophosphate	CAS-No.: 7320-34-5	1 – 5

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a

physician immediately.

First-aid measures after skin contact : Immediately flush skin with plenty of water for at least 30 minutes. Remove/Take off immediately

all contaminated clothing. Get immediate medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 20 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : Causes eye and skin burns. Severe corrosion to the respiratory tract at high concentrations. May

cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

Chronic symptoms : None known.

4.3. Immediate medical attention and special treatment, if necessary

Get immediate medical attention.

6/2/2022 (Issue date) EN (English US) 2/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

5.2. Specific hazards arising from the chemical

Fire hazard : This product is not classified as flammable or combustible.

Hazardous decomposition products in case of fire : Carbon oxides (CO, CO2). Phosphorus oxides. Metal oxides. Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Cool down the containers exposed to heat with a water spray.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Use self-contained breathing

apparatus and chemically protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Do not touch or walk on the spilled product. Do not get in eyes, on

skin, or on clothing. Wear suitable protective clothing. Do not breathe vapors. Ventilate spillage

area.

6.1.1. For non-emergency personnel

Emergency procedures : Avoid contact with eyes, skin and clothing. Do not breathe vapors.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container.

Other information : Place in a suitable container for disposal in accordance with the waste regulations (see Section

13).

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not get in eyes, on skin, or on clothing. Wear personal protective equipment. Wash hands

with water and soap. Do not breathe mist, vapors. Ensure good ventilation of the work station.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in corrosive resistant container with a resistant inner liner. Keep only in original container. Store in dry, cool, well-ventilated area. Keep container closed when not in use.

6/2/2022 (Issue date) EN (English US) 3/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

T-Greaser®

No additional information available

Tetrapotassium pyrophosphate (7320-34-5)

No additional information available

Sodium xylenesulfonate (1300-72-7)

No additional information available

Sodium Metasilicate Pentahydrate (10213-79-3)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation to minimize mist and/or vapor concentrations.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear impervious gloves. Consult supplier for specific recommendations.

Eye protection:

Use suitable eye protection. Goggles + face shield

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear. Pink. Liquid.

Color : Pink
Odor : Odorless

Odor threshold : No data available

pH : 10.8

Melting point : Not applicable Freezing point : -1 °C Boiling point : 107 °C

Flash point : No data available
Relative evaporation rate (butyl acetate=1) : Same as water
Flammability (solid, gas) : Not applicable.
Vapor pressure : 14 mm Hg @ 70°F
Relative vapor density at 20 °C : No data available

6/2/2022 (Issue date) EN (English US) 4/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative density : 1.1

Solubility : Soluble in water. Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available **Explosion limits** No data available Explosive properties No data available Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Metals.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Tetrapotassium pyrophosphate (7320-34-5)		
LD50 oral rat	2440 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 Inhalation - Rat	> 1.1 mg/l/4h	
ATE US (oral)	2440 mg/kg body weight	
Sodium xylenesulfonate (1300-72-7)		
LD50 oral rat	1000 mg/kg	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Sodium xylenesulfonate (1300-72-7)	
LD50 dermal rabbit	> 2000 mg/kg
ATE US (oral)	1000 mg/kg body weight
Sodium Metasilicate Pentahydrate (10213-79	l-3)
LD50 oral rat	1152 – 1349 mg/kg
LD50 dermal rat	> 5000 mg/kg
ATE US (oral)	1152 mg/kg body weight
Skin corrosion/irritation	Causes severe skin burns. pH: 10.8
Serious eye damage/irritation	Causes serious eye damage. pH: 10.8
Respiratory or skin sensitization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Tetrapotassium pyrophosphate (7320-34-5)	
NOAEL (oral,rat,90 days)	500 mg/kg body weight
Aspiration hazard	Not classified
Viscosity, kinematic	No data available
Symptoms/effects	Causes eye and skin burns. Severe corrosion to the respiratory tract at high concentrations. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.
Chronic symptoms	None known.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Tetrapotassium pyrophosphate (7320-34-5)	
LC50 - Fish [1]	> 100 mg/l Oncorhynchus mykiss (Rainbow trout)
EC50 - Crustacea [1]	> 100 mg/l Daphnia magna (Water flea)
Sodium Metasilicate Pentahydrate (10213-79-3)	
LC50 - Fish [1]	210 mg/l Brachydanio rerio (zebra-fish)
EC50 - Crustacea [1]	1700 mg/l Daphnia magna (Water flea)
ErC50 algae	> 345.4 mg/l Scenedesmus subspicatus

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste) : Dispose of in accordance with applicable federal, state, and local regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with DOT / IMDG / IATA

DOT	IMDG	IATA	
14.1. UN number			
3266	3266	3266	
14.2. Proper Shipping Name			
Corrosive liquid, basic, inorganic, n.o.s. (Sodium Metasilicate Pentahydrate)	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium Metasilicate Pentahydrate)	Corrosive liquid, basic, inorganic, n.o.s. (Sodium Metasilicate Pentahydrate)	
14.3. Transport hazard class(es)			
8	8	8	
Not applicable	8	8	
14.4. Packing group			
II	II	II	
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	
No supplementary information available			

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN3266

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

: 386 - Notwithstanding the provisions of §177.834(I) of this subchapter, cargo heaters may be used when weather conditions are such that the freezing of a wetted explosive material is likely. Shipments must be made by private, leased or contract carrier vehicles under exclusive use of the offeror. Cargo heaters must be reverse refrigeration (heat pump) units. Shipments made in accordance with this Special provision are excepted from the requirements of §173.60(b)(4) of this subchapter.

B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 : 1 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters",52 - Stow "separated from" acids

IMDG

Special provision (IMDG): 274Limited quantities (IMDG): 1 LExcepted quantities (IMDG): E2Packing instructions (IMDG): P001IBC packing instructions (IMDG): IBC02Tank instructions (IMDG): T11Tank special provisions (IMDG): TP2, TP27

EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE EmS-No. (Spillage) : S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES

Stowage category (IMDG) : B

Properties and observations (IMDG) : Reacts violently with acids. Causes burns to skin, eyes and mucous membranes.

IATA

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y840
PCA limited quantity max net quantity (IATA) : 0.5L
PCA packing instructions (IATA) : 851
PCA max net quantity (IATA) : 1L
CAO packing instructions (IATA) : 855
CAO max net quantity (IATA) : 30L

6/2/2022 (Issue date) EN (English US) 8/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Special provision (IATA) : A3, A803 ERG code (IATA) : 8L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Sodium Metasilicate Pentahydrate CAS-No. 10213-79-3 1 - 10%

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Tetrapotassium pyrophosphate (7320-34-5)

Listed on the Canadian DSL (Domestic Substances List)

Sodium xylenesulfonate (1300-72-7)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Sodium xylenesulfonate (1300-72-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Sodium Metasilicate Pentahydrate (10213-79-3)

Listed on the Canadian DSL (Domestic Substances List)

All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory

15.3. US State regulations



This product can expose you to 2,6-xylidine, 2,6-dimethylaniline, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H290	May be corrosive to metals
H314	Causes severe skin burns and eye damage

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phra	ases
H318	Causes serious eye damage

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.