



TRIDENT MARINE®

TRIDENT BLUE CORA-SIL MARINE EXHAUST & WATER



252V Series

Trident Wet exhaust and water coolant hose offers the BEST performance and flexibility. Silicone naturally handles higher temperatures and will last longer than rubber exhaust Hose. The silicone will also transfer less heat into the engine room. Meets and exceeds Marine Exhaust Standards, SAE J2006, ISO 13363 and is Lloyds Register Certified. 10-year warranty.

Specifications

Tube & Cover:
Wire reinforced
Corrugated silicone

Color: Blue

Reinforcement:
Wire helix and
2-ply polyester

Temperature Range:
350°F (177°C)

Coils:
60'(18.3m)

Lengths:
3'(.91m)
6'(1.83m)
12'(3.65m)

*Burst Pressure is 4 x Working Pressure

Part Number	ID		OD		Working Pressure		Weight		Bend Radius	
	in.	mm.	in.	mm.	Psi	Bar	Lb./ft.	Kg/m	In	mm
252v0340	3/4	19.1	1.25	31.8	87.5		8		3	76.2
252v0780	7/8	22.2	1.275	32.4	78.8		9		3.5	88.9
252v1000	1	25.4	1.5	38.1	70		9		3.5	88.9
252v1180	1-1/8	28.6	1.625	41.3	70		8		4	101.6
252v1560	1-5/16	33.3	1.81	46	57.5		12		5.25	133.4
252v1380	1-3/8	34.9	1.875	47.6	52.5		8		5.5	139.7
252v1140	1-1/4	31.8	1.75	44.5	62.5		11		4	101.6
252v1120	1-1/2	38.1	2	50.8	52.5		9		4.5	114.3
252v1580	1-5/8	41.3	2.125	54	52.5		13		6	152.4
252v1340	1-3/4	44.5	2.25	57.2	41.3		9		5	127
252v1780	1-7/8	47.6	2.375	60.3	41.3		14		6.5	165.1
252v2000	2	50.8	2.6	66	41.3		15		6.5	165.1
252v2180	2-1/8	54	2.725	69.2	36.3		17		8.5	215.9
252v2140	2-1/4	57.2	2.85	72.4	31.3		14		9	228.6
252v2380	2-3/8	60.3	2.975	75.6	27.5		21		9.5	241.3
252v2120	2-1/2	63.5	3.1	78.7	27.5		17		10	254
252v2580	2-5/8	66.7	3.225	81.9	27.5		21		10	254
252v2340	2-3/4	69.9	3.35	85.1	27.5		20		9	228.6
252v2780	2-7/8	73	3.475	88.3	27.5		21		10.5	266.7
252v3000	3	76.2	3.6	91.4	27.5		22		11	279.4
252v3180	3-1/8	79.4	3.725	94.6	26.3		21		12.5	317.5
252v3140	3-1/4	82.6	3.85	97.8	25		21		13	330.2
252v3120	3-1/2	88.9	4.1	104.1	23.8		21		13	330.2
252v4000	4	102	4.7	119.4	20		24		20	508
252v4120	4-1/2	114	5.2	132.1	20		32		22.5	571.5
252v5000	5	127	5.7	144.8	20		40		25	635
252v6000	6	152	6.7	170.2	20		48		30	762
252v8000	8	203	8.8	223.5	27.5		56		NA	NA
252v10000	10	254	10.7	271.8	27.5		NA		NA	NA
252v12000	12	305	12.7	322.6	17.5		NA		NA	NA
252v14000	14	356	14.7	373.4	17.5		NA		NA	NA
252v16000	16	406	16.7	424.2	13.8		NA		NA	NA
252v18000	18	457	18.7	475	NA		NA		NA	NA