



TRIDENT MARINE®

CORRUGATED MARINE WET EXHAUST (SAE J2006 & LLOYD'S)



252 Series

Trident Corrugated Wet Exhaust and Water Marine Hose offers best performance and bend radius with its High Temp EPDM Rubber compounds. This enables it to handle higher temperatures, longer life and durability that its competition. Exceeds SAE J2006-R2, and ABYC & NMMA P-1 exhaust standards and Lloyd's Registry Type Approved. Black High Temp EDPM Rubber 280°F (138°C) Max. *

Specifications	Part Number	ID		OD		Working Pressure		Weight		Bend Radius	
		in.	mm.	in.	mm.	Psi	Bar	Lb./50 ft.	Kg/m	in	mm
Construction:											
Tube & Cover: High Temp EPDM Rubber	252-1120	1-1/2	38	2	51	60	4.1	42		3	76.2
	252-1580	1-5/8	42	2.13	54	50	3.4	56		3.5	90
	252-1340	1-3/4	45	2.28	58	50	3.4	56		3.75	95.2
Color: Black	252-1780	1-7/8	48	2.38	60.5	50	3.4	58		4	101.6
	252-2000	2	50.8	2.5	63.5	50	3.4	62		4.5	113.5
Reinforcement: Multi-ply, High Tenacity Polyester, Steel Helix	252-2380	2-3/8	60	2.87	73	50	3.4	76		5.5	139.7
	252-2120	2-1/2	63.5	3.06	78	50	3.4	75		6	152.4
	252-2780	2-7/8	73	3.44	87.5	50	3.4	100		7.5	190.5
	252-3000	3	76.2	3.61	91.5	50	3.4	124		8	203.2
	252-3180	3-1/8	80	3.76	95.5	50	3.4	144		8.25	209.6
Temperature Range: 280°F (138°C)	252-3120	3-1/2	90	4.15	105.5	50	3.4	128		9	228.6
	252-4000	4	101.6	4.62	117.5	50	3.4	152		10	254
	252-5000	5	127	5.75	146	50	3.4	248		14	355.6
Coils: 50' (15.24m)	252-6000	6	152.4	6.75	171.5	48	3.3	272		18	457.2
	252-8000	8	203	8.88	225.5	42	2.9	304		40	1016

*Burst Pressure is 4 x Working Pressure

Lengths:

6.25' (1.9m)
12.5' (3.81m)