

# PREMIUM MARINE SANITATION HOSE



# 101 Series

**Trident** Premium Sanitation Hose resistant to odor permeation. Simply the BEST solution for marine environments, built with EPDM rubber to ensure the over all performance and resistance to odor permeation that you would expect in a sanitation hose. Excellent bend radius and heat resistance (a big contributor to odor permeation on plastic hoses). 10 Year Warranty.

<b>Tube &amp; Cover:</b> EDPM/SBR Rubber	Part Number	ID		OD		Working Pressure		Weight		Bend Radius	
Color: Black w/Green Stripe		in.	mm.	in.	mm.	Psi	Bar	Lb./50 ft.	Kg/ 15.24m	in	mm
	101-1000	1	25.4	1.42	36	80	5.5	32	14.5	1.46	37
Reinforcement: Polyester reinforcement	101-1120 101-1780	1 1/2 1 7/8	38.1 47.6	2 2.38	50.8 60.3	60 50	4.1 3.4	44 64	19.9 29	3 5.75	76.2 146

+ spring steel wire helix

Temperature Range:

-20F-220°F (-29°C-104°C)

**Coils:** 50' (15m) **Lengths:** 12.5' (3.8m) \*Burst Pressure is 4 x Working Pressure



# PREMIUM MARINE SANITATION HOSE



## # 102 Series

**Trident** Premium Sanitation Hose resistant to odor permeation. Simply the BEST solution for marine environments, built with EPDM rubber to ensure the over all performance and resistance to odor permeation that you would expect in a sanitation hose. Excellent bend radius and heat resistance (a big contributor to odor permeation on plastic hoses). 10 Year Warranty.

### Specifications

Construction: Tube & Cover:	Part Number	ID		OD		Working Pressure		Weight		Bend Radius	
EDPM/SBR Rubber		in.	mm.	in.	mm.	Psi	Bar	Lb./50 ft.	Kg/15.24 m	in	mm
White w/Green Stripe	102-1000W 102-1120W	1 1-1/2	25.4 38.1	1.42 2	36 50.8	80 60	5.5 4.1	32 44	14.5 19.9	1.46 3	37 76.2
Reinforcement:	102-2000W	2	50.8	2.45	62.2	40	2.8	70	31.7	2.45	62.2

### Reinforcement:

Polyester reinforcement + spring steel wire helix

### Temperature Range:

-20F-220°F (-29°C-104°C)

**Coils:** 50' (15m) **Lengths:** 12.5' (3.8m) \*Burst Pressure is 4 x Working Pressure