

# WX TUBING DATASHEET



Munster Simms Engineering Ltd.  
 2 Enterprise Road, Bangor, BT19 7TA, N. Ireland  
 tel: +44 (0)28 9127 0531 info@whalepumps.com whalepumps.com

Whale's WX Polythene Tubing				
Description	Standard Tubing		High Performance Tubing	
<b>Material</b>	MDPE (Medium density Polyethylene)		MDPE (Medium density Polyethylene)	
<b>Types</b>	Cold/Blue Tubing	Hot/Red Tubing	Cold/Blue Tubing	Hot/Blue Tubing
<b>Maximum Pressure (Safe working limit)</b>	12 bar (180 psi) @20°C(68°F)	6 bar (90 psi) @65°C(150°F)	12 bar (180 psi) @20°C(68°F)	7.5 bar (110 psi) @65°C(150°F)
<b>Maximum Temperature</b>	65°C		82°C	
<b>Minimum bend radius</b>	75mm		75mm	
<b>Outer Diameter</b>	15.0mm +/-0.1mm			
<b>Internal Diameter</b>	11.0mm +/- 0.1mm	10.0mm +/10.1mm	10.0mm +/-0.1mm	
<b>Additional Notes</b>			Scratch resistant surface	
<b>Certifications</b>	<ul style="list-style-type: none"> <li>EU Directive 10/2011 – plastics and articles that come into contact with food</li> </ul>		<ul style="list-style-type: none"> <li>EU Directive 10/2011 – plastics and articles that come into contact with food</li> <li>NSF-61</li> </ul>	
<b>Warranty</b>	3 years		10 years	

Green tubing is intended for cold/raw water only and has the same properties whether it is the standard of Whalex version.