

## Chain grip kit 2994 - Rope 12 mm - Length 4m

Part #29944



### Description

Complete chain grip kit  
Ready to use  
No splicing knowledge required  
Kit includes: 1 stainless steel chain grip and 1 pre-spliced twisted 3 strand polyester  
Wear indicator  
Rope dia: 12 mm (15/32) – Length: 4 m (13 feet 1 31/64 inches)  
Dia mooring line: 8 mm (5/16)  
Part # chain grip: 2994  
Color: black / blue

### Applications

Mooring - suitable for sailing and motor boats

### Technical information

Materials	Duplex stainless steel grade - polyester
Rope size	12
Working load (kg)	480
Weight (g)	600

### Caption

	Working load (WL) : for nautical applications
	Working Load Limit (WLL): for industrial applications only. The safety factor is 5 times the breaking load. WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

## Chain grip kit 2995 - Rope 12 mm - Length 5m

Part #29955



### Description

Complete chain grip kit  
Ready to use  
No splicing knowledge required  
Kit includes: 1 stainless steel chain grip and 1 pre-spliced twisted 3 strand polyester  
Wear indicator  
Rope dia: 12 mm (15/32 inch) – Length: 5 m (16 feet 4 27/32 inches)  
Dia mooring line: 10 mm (25/64 inch)  
Part # chain grip: 2995  
Color: black / blue

### Applications

Mooring - suitable for sailing and motor boats

### Technical information

Materials	Duplex stainless steel grade - Polyester
Rope size	12
Working load (lb)	1580
Weight (lb)	1.631

### Caption



Working load (WL) : for nautical applications



Working Load Limit (WLL): for industrial applications only.

The safety factor is 5 times the breaking load.  
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

## Chain grip kit 2996 - Rope 16 mm - Length 6m

Part #29966



### Description

Complete chain grip kit  
Ready to use  
No splicing knowledge required  
Kit includes: 1 stainless steel chain grip and 1 pre-spliced twisted 3 strand polyester  
Wear indicator  
Rope dia: 16 mm (5/8 inch) – Length: 6 m (19 feet 8 7/32 inches)  
Dia mooring line: 12 mm (15/32 inch)  
Part # chain grip: 2996  
Color: black / blue

### Applications

Mooring - Suitable for sailing and motor boats

### Technical information

Materials	Duplex stainless steel grade - polyester
Rope size	16
Working load (lb)	2110
Weight (lb)	3.307

### Caption

	Working load (WL) : for nautical applications
	Working Load Limit (WLL): for industrial applications only. The safety factor is 5 times the breaking load. WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.